

CITY OF LONGVIEW, TEXAS

2002 MAPPING & MONUMENTATION PROJECT. HORIZONTAL & VERTICAL CONTROL NETWORK.

LONGVIEW CITY LIMITS AND EXTRATERRITORIAL JURISDICTION, GREGG, UPSHUR, HARRISON AND RUSK COUNTIES





JOHNSON & PACE

ENGINEERING & SURVEYING CONSULTANTS 430 NORTH CENTER STREET, SUITE A LONGVIEW, TEXAS 75601

PHONE: 903-753-0663 FAX: 903-753-8803

www.jpesc.com

JOB NUMBER 1994-001 DATE: APRIL 2002

SURVEYORS REPORT:

OUR JOB NUMBER 1994-001 2002 GPS HORIZONTAL & VERTICAL CONTROL SURVEY CITY OF LONGVIEW, TEXAS.

SURVEYING FIRM: Johnson & Pace, Engineering & Surveying Consultants, 430 North Center Street, Longview, TX 75601, Project supervision by Lonnie C. Pace, II, Professional Land Surveyor, Texas Registration No. 1573.

CLIENT: The Survey was performed for the City of Longview, Texas, under a subcontract with MD Atlantic Technologies, Inc., 2227 Drake Avenue SW, Building 14, Huntsville, Alabama, 35805, Telephone: 256-882-7788, (MD Atlantic) Project Management by Chris Jaeger.

PROJECT LOCATION: The primary area of concern was the Extraterritorial Jurisdiction (ETJ) of the City of Longview, Texas.

PURPOSE: The Survey was performed to establish thirty-one (31) CITY SURVEY MARKERS (CSM's) in the Longview ETJ for two purposes, 1. To provide horizontal and vertical control for aerial mapping of the ETJ, and 2. To provide horizontal and vertical control for Conventional Surveying.

EQUIPMENT: Two types of GPS surveying were performed in the scope of this project, "Static GPS" and "Airborne GPS Control"(ABGPS). The Static surveying was performed "Ashtech Locus" and "Ashtech ProMark II" single frequency GPS units. The ABGPS was performed using "Leica 530" and "Trimble 4000SSE" dual frequency GPS units.

HORIZONTAL DATUM: This Survey is based upon the Texas Coordinate System of 1983, North Central Zone, and referenced (constrained) to National Geodetic Survey (NGS) Stations: "FAA GGG A" (PID AB2804) at Gregg County Airport, "FAA 07F a 1994" (PID AB2798) at Gladewater Municipal Airport, "4F4 A 1994" (PID AB2783) at Gilmer-Upshur County Airport, "FAA ASL A 1994" (PID AB2800) at Harrison County Airport, and "FAA F12 A 1994" (PID AB2804) at Rusk County Airport. (Sketches attached)

VERTICAL DATUM: This Survey is based upon the North American Vertical Datum of 1988 (NAVD 88) and constrained (referenced) to NGS Station "E-160" located at the Gregg County Courthouse (Sketch attached)

SPECIFICATIONS: MD Atlantic specified that the work be performed to Order 2-I Standards, that is a Line Length Dependent Error maximum of 1 part in 50,000, (1:50,000) and considering that the end product was to be maps at a scale of 1 inch equals 100 feet (1"=100") with contours at 2 foot intervals, the vertical positions were to be accurate with a tolerance of +/- one tenth of a foot (0.10") to a 95% confidence level.

PROJECT SUMMARY:

The GPS Survey was conducted in three phases, Primary Control, ETJ Control, and Azimuth Control.

Primary Control Network:

Johnson & Pace had previously established a Horizontal and Vertical Control Network connecting the NGS Stations previously cited in "Horizontal Datum" and this project required such a network as its basis. One control site requested in this contract was located very close to one of our established markers in the Hallsville, Texas area, so we replaced our marker with CSM 1211 and reran the GPS Survey on this network for use as Primary Control. The Network Relative Accuracy for this GPS network ranged from a low of 1part in 603,000 Horizontal, and 1 part in 474,000 Vertical, to a high of 1part in 1,223,000 Horizontal and 1part in 989,000 Vertical.

ETJ Control Network:

The positions established in the Primary Control Network for markers CSM 1211, 0105 (FAA GGG A), 0102, 0104 and 0115 were held to constrain a GPS network which encompassed the City of Longview ETJ and established CSM's at thirty one (31) locations selected by MD Atlantic. The Network Relative Accuracy for this GPS network ranged from a low of 1part in 477,000 Horizontal, and 1part in 301,000 Vertical, to a high of 1part in 2,300,000 Horizontal and 1 part in 1,541,000 Vertical.

Azimuth Control Networks:

The positions established in the Primary and ETJ Control networks were held to constrain GPS networks which established Azimuth (Reference) CSM's as companion markers near each of the CSM's established in the ETJ Control network. The Network Relative Accuracy for these GPS networks ranged from a low of 1part in 106,000 Horizontal, and 1part in 53,000 Vertical, to a high of 1part in 3,205,000 Horizontal and 1 part in 2,523,000 Vertical. (The low ratios occurred on a short vector with a length of 2200 feet, which produced probable errors of 0.02 foot horizontal and 0.04 foot vertical)

VERTICAL STATEMENT:

The Published NGS Data Sheets for the Stations listed in "Horizontal Datum" contain the following Note.

"GPS derived orthometric heights for airport stations designated as Primary Airport Control Stations or Secondary Airport Control Stations are published to 2 decimal places. This maintains centimeter relative accuracy between the PACS and SACS. It does not indicate centimeter accuracy relative to other marks which are part of the NAVD 88 network."

Therefore based upon NGS Station E-160, (published elevation = 355.32) we set a control point (#0132) near the Gregg County Courthouse on the grounds of the Gregg County Jail with an elevation of 375.02 feet established by conventional Surveying methods. The ETJ Control Network vertical value for this point was 375.10 feet, a variance of 0.08 foot, which is within the specified tolerance of +/ 0.10 foot. As such we can certify that all of the Control Networks in this project are based upon NAVD 88.

CONCLUSION: Attached are the following:

- A. Data Sheets for NGS Control Markers.
- B. Photographs for City Survey Markers and Johnson & Pace Markers.

C. Data Sheets (Sketches) or City Survey Markers and Johnson & Pace Markers.

Lonnie C. Pace, II Professional Land Surveyor Texas Registration No. 1573



TYPICAL "CITY SURVEY MARKER"
5/8" X 5' REBAR SET IN " X 2' CONCRETE PILLAR
WITH 3-1/4" DOMED ALUMINUM CAP

INDEX

NGS Data Sheet For Station "FAA 07F A 1994"	(0101, Gladewater Airport)	6
NGS Data Sheet For Station "4F4 A 1994"	(0103, Gilmer Airport)	8
NGS Data Sheet For Station "FAA GGG A"	(0105, Gregg Co Airport)	10
NGS Data Sheet For Station "FAA ASL: A 1994"	' (0112, Harrison Co Airport)	13
NGS Data Sheet For Station "FAA F12 A 1994"	(0117, Rusk County Airport)	15
NGS Data Sheet For Station "E-160"	(Gregg County Courthouse)	17
Primary Control Schematic		19
Primary Control Geodetic Positions		20 - 21
Primary Control Grid Positions		22 – 24
ETJ Control Schematics		25 – 26
ETJ Control Geodetic Positions		27 - 29
ETJ Control Grid Positions		30 - 34
5467665454	10	05 74
PHOTOGRAPH	IS	35 - 74

STATION FAA 07F A 1994 - GLADEWATER MUNICIPAL AIRPORT

```
National Geodetic Survey, Retrieval Date = MAY 3, 2001
*****************
AB2798 PACS - This is a Primary Airport Control Station.
AB2798 DESIGNATION - FAA 07F A 1994
AB2798 PID - AB2798
AB2798 STATE/COUNTY- TX/GREGG
AB2798 USGS QUAD - GLADEWATER (1960)
AB2798
AB2798
                             *CURRENT SURVEY CONTROL
AB2798
AB2798* NAD 83(1993) - 32 31 34.13033(N) 094 57 56.79070(W)
                                                              ADJUSTED
AB2798* NAVD 88
                           87.46 (meters) 286.9 (feet) GPS OBS
AB2798
AB2798 X
                       -465,953.000 (meters)
                                                               COMP
AB2798 Y
                   - -5,362,760.154 (meters)
                                                               COMP
                  - 3,409,801.155 (meters)
AB2798 Z
                                                               COMP
AB2798 LAPLACE CORR-
                              0.09 (seconds)
                                                              DEFLEC99
AB2798 ELLIP HEIGHT-
                             61.04 (meters)
                                                              GPS OBS
AB2798 GEOID HEIGHT-
                           -26.34 (meters)
                                                              GEOID99
AB2798
AB2798 HORZ ORDER - B
AB2798 ELLP ORDER - FOURTH CLASS II
AB2798
AB2798. This mark is at Gladewater Muni (07F) Airport (07F)
AB2798. The horizontal coordinates were established by GPS observations
AB2798.and adjusted by the National Geodetic Survey in February 1996.
AB2798
AB2798. The orthometric height was determined by GPS observations and a
AB2798.high-resolution geoid model.
AB2798
AB2798.GPS derived orthometric heights for airport stations designated as
AB2798.PACS or SACS are published to 2 decimal places. This maintains
AB2798.centimeter relative accuracy between the PACS and SACS. It does
AB2798.not indicate centimeter accuracy relative to other marks which are
AB2798.part of the NAVD 88 network.
AB2798
AB2798. X, Y, and Z were computed from the position and the ellipsoidal ht.
AB2798. The Laplace correction was computed from DEFLEC99 derived deflections.
AB2798
AB2798. The ellipsoidal height was determined by GPS observations
AB2798.and is referenced to NAD 83.
AB2798. The geoid height was determined by GEOID99.
AB2798
```

```
AB2798;
                          North
                                       East Units Scale
AB2798; SPC TXNC
                   - 2,100,892.626 931,947.812 MT 0.99991439 +1 55 39.2
                   - 3,600,460.932 315,374.764 MT 1.00002034 -1 03 26.2
AB2798;UTM 15
AB2798
AB2798
                               SUPERSEDED SURVEY CONTROL
AB2798
AB2798 ELLIP HT
                              61.09 (m)
                                                             GP(
                                                                     ) 1 1
AB2798
AB2798. Superseded values are not recommended for survey control.
AB2798.NGS no longer adjusts projects to the NAD 27 or NGVD 29 datums.
AB2798. See file dsdata.txt to determine how the superseded data were derived.
AB2798
AB2798 MARKER: I = METAL ROD
AB2798 SETTING: 59 = STAINLESS STEEL ROD IN SLEEVE (10 FT.+)
AB2798 STAMPING: FAA 07F A 1994
AB2798 PROJECTION: FLUSH
AB2798 MAGNETIC: I = MARKER IS A STEEL ROD
AB2798 STABILITY: B = PROBABLY HOLD POSITION/ELEVATION WELL
AB2798 SATELLITE: THE SITE LOCATION WAS REPORTED AS SUITABLE FOR
AB2798+SATELLITE: SATELLITE OBSERVATIONS - 1994
AB2798 ROD/PIPE-DEPTH: 8.4 meters
AB2798 SLEEVE-DEPTH : 0.90 meters
AB2798
AB2798 HISTORY
                   - Date
                              Condition
                                               Recov. By
AB2798 HISTORY
                   - 1994
                              MONUMENTED
                                               NGS
AB2798
AB2798
                               STATION DESCRIPTION
AB2798
AB2798'DESCRIBED BY NATIONAL GEODETIC SURVEY 1994 (AJL)
AB2798'THE STATION IS LOCATED ABOUT 2.5 KM (1.55 MI) SOUTHWEST OF GLADEWATER
AB2798'AT THE GLADEWATER MUNICIPAL AIRPORT, IN GRASS ADJACENT TO A DRAINAGE
AB2798'DITCH IN THE SOUTHEAST CORNER OF THE AIRFIELD AND ALONG THE ENTRANCE
AB2798'ROAD. OWNERSHIP--CITY OF GLADEWATER, C/O SHARON JOHNSON, P.O. BOX
AB2798'551, GLADEWATER, TX 75647. PHONE 903-845-2196. TO REACH FROM THE
AB2798'JUNCTION OF U.S. HIGHWAY 271 AND STATE HIGHWAY 135, ABOUT 3 KM (1.85
AB2798'MI) SOUTHWEST OF GLADEWATER, GO NORTHEAST ON HIGHWAY 271 FOR 0.6 KM
AB2798'(0.35 MI) TO THE AIRPORT ENTRANCE ROAD ON THE LEFT. TURN LEFT, NORTH,
AB2798'ON ENTRANCE ROAD FOR 0.07 KM (0.05 MI) TO THE STATION ON THE LEFT.
AB2798'THE STATION MARK IS A PUNCH HOLE TOP CENTER OF A STAINLESS STEEL ROD
AB2798'IN A GREASE FILLED SLEEVE 90 CM LONG ENCASED IN A 12.7 CM PVC PIPE
AB2798'WITH A LOGO CAP SURROUNDED BY CONCRETE SET FLUSH WITH THE GROUND. IT
AB2798'IS 74.1 M (243.1 FT) NORTHWEST OF THE CENTER OF THE HIGHWAY, 37.2 M
AB2798'(122.0 FT) NORTHWEST OF THE NORTH LEG OF THE AIRPORT SIGN, ABOUT 15 M
AB2798'(49.2 FT) SOUTHEAST OF THE DITCH, 12.1 M (39.7 FT) SOUTHWEST OF THE
AB2798'CENTER OF THE ENTRANCE ROAD, AND 1.0 M (3.3 FT) NORTHEAST OF A
AB2798'FIBERGLASS WITNESS POST. DESCRIBED BY D.G. AUG
```

NGS STATION: 4F4 A 1994 - GILMER-UPSHUR COUNTY AIRPORT

```
National Geodetic Survey, Retrieval Date = MAY 3, 2001
******************
AB2783 PACS - This is a Primary Airport Control Station.
AB2783 DESIGNATION - 4F4 A 1994
AB2783 PID - AB2783
AB2783 STATE/COUNTY- TX/UPSHUR
AB2783 USGS QUAD - GILMER (1978)
AB2783
AB2783
                             *CURRENT SURVEY CONTROL
AB2783
AB2783* NAD 83(1993) - 32 42 11.99241(N) 094 56 54.90254(W)
                                                             ADJUSTED
AB2783* NAVD 88
                          126.03 (meters) 413.5 (feet) GPS OBS
AB2783
AB2783 X
                  - -463,433.135 (meters)
                                                              COMP
                  - -5,352,380.628 (meters)
AB2783 Y
                                                               COMP
                  - 3,426,372.941 (meters)
AB2783 Z
                                                              COMP
AB2783 LAPLACE CORR- -0.20 (seconds)
                                                              DEFLEC99
AB2783 ELLIP HEIGHT-
                            99.50 (meters)
                                                             GPS OBS
AB2783 GEOID HEIGHT-
                           -26.47 (meters)
                                                             GEOID99
AB2783
AB2783 HORZ ORDER - B
AB2783 ELLP ORDER - FOURTH CLASS II
AB2783
AB2783. This mark is at Gilmer-Upshur Co (4F4) Airport (4F4)
AB2783. The horizontal coordinates were established by GPS observations
AB2783.and adjusted by the National Geodetic Survey in February 1996.
AB2783
AB2783. The orthometric height was determined by GPS observations and a
AB2783.high-resolution geoid model.
AB2783
AB2783.GPS derived orthometric heights for airport stations designated as
AB2783.PACS or SACS are published to 2 decimal places. This maintains
AB2783.centimeter relative accuracy between the PACS and SACS. It does
AB2783.not indicate centimeter accuracy relative to other marks which are
AB2783.part of the NAVD 88 network.
AB2783
AB2783. X, Y, and Z were computed from the position and the ellipsoidal ht.
AB2783. The Laplace correction was computed from DEFLEC99 derived deflections.
AB2783
AB2783. The ellipsoidal height was determined by GPS observations
AB2783.and is referenced to NAD 83.
AB2783
AB2783. The geoid height was determined by GEOID99.
```

```
AB2783
                        North
                                    East Units Scale
AB2783;SPC TXNC - 2,120,583.200 932,897.792 MT 0.99989098 +1 56 12.9
                - 3,620,077.472 317,349.885 MT 1.00001138 -1 03 11.1
AB2783;UTM 15
AB2783
AB2783|------
AB2783 | PID Reference Object
                                           Distance Geod. Az |
                                                dddmmss.s |
                                         394.135 METERS 18018 |
AB2783| CR1361 GILPORT
AB2783|------
AB2783
AB2783
                             SUPERSEDED SURVEY CONTROL
AB2783
AB2783 ELLIP HT -
                            99.55 (m)
                                                         GP( ) 1 1
AB2783
AB2783. Superseded values are not recommended for survey control.
AB2783.NGS no longer adjusts projects to the NAD 27 or NGVD 29 datums.
AB2783. See file dsdata.txt to determine how the superseded data were derived.
AB2783
AB2783 MARKER: I = METAL ROD
AB2783 SETTING: 59 = STAINLESS STEEL ROD IN SLEEVE (10 FT.+)
AB2783 STAMPING: 4F4 A 1994
AB2783 PROJECTION: FLUSH
AB2783 MAGNETIC: I = MARKER IS A STEEL ROD
AB2783 STABILITY: B = PROBABLY HOLD POSITION/ELEVATION WELL
AB2783 SATELLITE: THE SITE LOCATION WAS REPORTED AS SUITABLE FOR
AB2783+SATELLITE: SATELLITE OBSERVATIONS - 1994
AB2783 ROD/PIPE-DEPTH: 8.6. meters
AB2783 SLEEVE-DEPTH : 0.90 meters
AB2783
AB2783 HISTORY - Date Condition
AB2783 HISTORY - 1994 MONUMENTED
                                           Recov. By
                                            NGS
AB2783
AB2783
                             STATION DESCRIPTION
AB2783'DESCRIBED BY NATIONAL GEODETIC SURVEY 1994 (AJL)
AB2783'THE STATION IS LOCATED ABOUT 3 KM (1.85 MI) SOUTH OF GILMER, AT THE
AB2783'GILMER-UPSHUR COUNTY AIRPORT, IN THE CENTER OF THE NORTHEND OF THE
AB2783'GRASS ISLAND OF THE TURN AROUND AT RUNWAY END 17. OWNERSHIP--CITY OF
AB2783'GILMER, BOX 760, GILMER, TX 75644. CITY MANAGER IS TIM GUMP. PHONE
AB2783'903-843-2552. TO REACH FROM THE JUNCTION OF U.S. HIGHWAY 271 AND
AB2783'STATE HIGHWAY 155 ON THE SOUTH SIDE OF GILMER, GO SOUTH ON U.S.
AB2783'HIGHWAY 271 FOR 1.1 KM (0.70 MI) TO THE AIRPORT ENTRANCE ROAD ON THE
AB2783'RIGHT (AVIATION DRIVE) . TURN RIGHT, TURN RIGHT, WEST, ON THE
AB2783'ENTRANCE ROAD FOR 0.4 KM (0.25 MI) TO A GATE. PASS THROUGH GATE,
AB2783'WEST, FOR 0.16 KM (0.10 MI) CROSSING APRON AND ALONG TAXI TO THE
AB2783'RUNWAY. TURN RIGHT, NORTH, ALONG RUNWAY FOR 0.41 KM (0.25 MI) TO THE
AB2783'STATION ON THE RIGHT. THE STATION IS A PUNCH HOLE TOP CENTER OF A
AB2783'STAINLESS STEEL ROD IN A 2.5 CM GREASE FILLED SLEEVE 90 CM LONG
AB2783'ENCASED IN A 12.7 CM PVC PIPE WITH A LOGO CAP SURROUNDED BY CONCRETE
AB2783'SET FLUSH WITH THE GROUND. IT IS 22.7 M (74.5 FT) EAST OF THE CENTER
AB2783'OF THE RUNWAY, 22.1 M (72.5 FT) WEST OF THE CENTER OF THE TURN AROUND,
AB2783'16.9 M (55.4 FT) SOUTH OF THE CENTER OF THE CONNECTOR, 11.5 M (37.7
AB2783'FT) SOUTHWEST OF THE CENTER OF A CONCRETE PAD FOR A CABLE LINE, AND
AB2783'0.4 M (1.3 FT) WEST OF A FIBERGLASS WITNESS POST. DESCRIBED BY D.G.
AB2783'AUG
```

(JOHNSON & PACE POINT No. 0105)

NGS STATION FAA GGG A - GREGG COUNTY AIRPORT

```
National Geodetic Survey, Retrieval Date = MAY 3, 2001
AB2804
******************
AB2804 PACS - This is a Primary Airport Control Station.
AB2804 DESIGNATION - FAA GGG A
AB2804 PID - AB2804
AB2804 STATE/COUNTY- TX/GREGG
AB2804 USGS QUAD - LAKEPORT (1983)
AB2804
AB2804
                             *CURRENT SURVEY CONTROL
AB2804
AB2804* NAD 83(1993) - 32 23 35.35432(N) 094 42 10.17601(W)
                                                             ADJUSTED
                         108.47 (meters) 355.9 (feet) GPS OBS
AB2804* NAVD 88 -
AB2804
AB2804 X
                       -441,987.207 (meters)
                                                               COMP
AB2804 Y
                   - -5,372,748.711 (meters)
                                                              COMP
AB2804 Z
                  - 3,397,368.169 (meters)
                                                              COMP
AB2804 LAPLACE CORR-
                             0.12 (seconds)
                                                              DEFLEC99
AB2804 ELLIP HEIGHT-
                             82.10 (meters)
                                                              GPS OBS
AB2804 GEOID HEIGHT-
                          -26.27 (meters)
                                                              GEOID99
AB2804
AB2804 HORZ ORDER - B
AB2804 ELLP ORDER - FOURTH CLASS II
AB2804. This mark is at Gregg Co (GGG) Airport (GGG)
AB2804. The horizontal coordinates were established by GPS observations
AB2804.and adjusted by the National Geodetic Survey in February 1996.
AB2804
AB2804. The orthometric height was determined by GPS observations and a
AB2804.high-resolution geoid model.
AB2804.GPS derived orthometric heights for airport stations designated as
AB2804.PACS or SACS are published to 2 decimal places. This maintains
AB2804.centimeter relative accuracy between the PACS and SACS. It does
AB2804.not indicate centimeter accuracy relative to other marks which are
AB2804.part of the NAVD 88 network.
AB2804
AB2804. X, Y, and Z were computed from the position and the ellipsoidal ht.
AB2804
AB2804. The Laplace correction was computed from DEFLEC99 derived deflections.
AB2804
AB2804. The ellipsoidal height was determined by GPS observations
AB2804.and is referenced to NAD 83.
AB2804. The geoid height was determined by GEOID99.
```

```
AB2804
                         North East Units Scale Converg.
AB2804;
AB2804; SPC TXNC - 2,087,016.829 957,167.474 MT 0.99993818 +2 04 15.4
                 - 3,585,290.452 339,838.901 MT 0.99991633 -0 54 44.8
AB2804;UTM 15
AB2804
AB2804:
                                                             Grid Az
                    Primary Azimuth Mark
AB2804:SPC TXNC
                 - FAA GGG C
                                                             219 23 32.6
AB2804:UTM 15 - FAA GGG C
                                                             222 22 32.8
AB2804| PID Reference Object
                                                Distance
                                                              Geod. Az |
AB28041
                                                               dddmmss.s |
AB2804| AB6207 FAA GGG C
                                                APPROX. 1.3 KM 2212748.0 |
                                                APPROX. 1.4 KM 2425956.5 |
AB2804| AB6206 FAA GGG B
AB2804|------|
AB2804
                             SUPERSEDED SURVEY CONTROL
AB2804
AB2804 ELLIP HT -
                            82.15 (m)
                                                           GP( ) 1 1
AB2804
AB2804. Superseded values are not recommended for survey control.
AB2804.NGS no longer adjusts projects to the NAD 27 or NGVD 29 datums.
AB2804. See file dsdata.txt to determine how the superseded data were derived.
AB2804 MARKER: DH = HORIZONTAL CONTROL DISK
AB2804 SETTING: 36 = VALVE VAULT
AB2804 STAMPING: FAA GGG A 1994
AB2804 MAGNETIC: N = NO MAGNETIC MATERIAL
AB2804 STABILITY: B = PROBABLY HOLD POSITION/ELEVATION WELL
AB2804 SATELLITE: THE SITE LOCATION WAS REPORTED AS SUITABLE FOR
AB2804+SATELLITE: SATELLITE OBSERVATIONS - March 07, 1997
AB2804 HISTORY - Date Condition
AB2804 HISTORY - 1994 MONUMENTED
                                             Recov. By
                                             NGS
AB2804 HISTORY - 19970307 GOOD
                                              NGS
AB2804
AB2804
                              STATION DESCRIPTION
AB2804
AB2804'DESCRIBED BY NATIONAL GEODETIC SURVEY 1994 (AJL)
AB2804'THE STATION IS LOCATED ABOUT 7 KM (4.35 MI) SOUTH OF LONGVIEW AT THE
AB2804'GREGG COUNTY AIRPORT, JUST INSIDE THE PERIMETER FENCE IN THE NORTHEAST
AB2804'CORNER OF THE AIRFIELD, AND ALONG AN ACCESS ROAD TO THE AIRFIELD.
AB2804'OWNERSHIP--GREGG COUNTY AIRPORT, HIGHWAY 322, LONGVIEW, TX 75603.
AB2804'AIRPORT MANAGER IS BUCKEY WALTERS. PHONE 903-643-3031. CONTACT HIM
AB2804'ONE DAY IN ADVANCE FOR PERMISSION TO OCCUPY THIS STATION. TO REACH
AB2804'FROM THE OVERPASS AT THE JUNCTION OF INTERSTATE HIGHWAY 20 AND STATE
AB2804'HIGHWAY 322 (EXIT 595) ON THE SOUTH OF LONGVIEW, GO SOUTH ON HIGHWAY
AB2804'322 FOR 3.44 KM (2.15 MI) TO A PAVED ROAD RIGHT JUST AFTER CROSSING
AB2804'THE SABINE RIVER. TURN RIGHT, SOUTHWEST, ON HIGHWAY 322 FOR 2.25 KM
AB2804'(1.40 MI) TO A PAVED ROAD LEFT. TURN LEFT, EAST, ON FARM ROAD 349 FOR
AB2804'1.87 KM (1.15 MI) TO A PAVED ROAD RIGHT. TURN RIGHT, SOUTH, ON JERRY
AB2804'LUCY ROAD FOR 0.18 KM (0.10 MI) TO THE STATION ON THE RIGHT AFTER THE
AB2804'SOUTH ONE OF TWO GATES. STATION IS SET FLUSH NEAR THE CENTER OF THE
AB2804'TOP OF A 1.8 M (5.9 FT) DIAMETER CONCRETE FOUNDATION OF A MANHOLE
AB2804'COVER PROJECTING 20 CM. IT IS 14.2 M (46.6 FT) WEST OF THE CENTER OF
AB2804'JERRY LUCY ROAD, 13.8 M (45.3 FT) SOUTH OF THE CENTER OF THE ACCESS
AB2804'ROAD, 11.8 M (38.7 FT) SOUTHWEST OF THE SOUTH GATE POST OF THE SOUTH
AB2804'ONE OF TWO GATES, 0.4 M (1.3 FT) NORTHEAST OF THE NORTHEAST EDGE OF A
AB2804'MANHOLE COVER, AND 6.1 M (20.0 FT) WEST OF A FIBERGLASS WITNESS POST.
```

AB2804 STATION RECOVERY (1997)
AB2804
AB2804'RECOVERY NOTE BY NATIONAL GEODETIC SURVEY 1997 (AJL)
AB2804'RECOVERY NOTE BY NATIONAL GEODETIC SURVEY 07 MAR 1997 (WCW).
AB2804'RECOVERED IN GOOD CONDITION AS DESCRIBED WITH CHANGES. THE STATION IS
AB2804'SET INTO THE TOP OF A PREFABRICATED CONCRETE VALVE VAULT. THE VAULT
AB2804'IS 1.8 M (5.9 FT) DIAMETER, 1.5 M (4.9 FT) DEEP TO GRAVEL FLOOR, AND
AB2804'THE TOP SLAB IS 0.3 M (1.0 FT) THICK. THE STATION IS LOCATED 19.1 M
AB2804'(62.7 FT) WEST OF JERRY LUCY ROAD CENTER. NOTE--THIS IS A PRIMARY
AB2804'AIRPORT CONTROL STATION (PACS).

(JOHNSON & PACE POINT No. 0112)

NGS STATION FAA ASL A 1994 - HARRISON COUNTY AIRPORT

```
National Geodetic Survey, Retrieval Date = MAY 3, 2001
AB2800
******************
                 - This is a Candidate for Federal Base Network Control.
AB2800 PACS - This is a Primary Airport Control Station.
AB2800 DESIGNATION - FAA ASL A 1994
AB2800 PID - AB2800
AB2800 STATE/COUNTY- TX/HARRISON
AB2800 USGS QUAD - MARSHALL EAST (1978)
AB2800
AB2800
                            *CURRENT SURVEY CONTROL
AB2800
AB2800* NAD 83(1993) - 32 31 13.75733(N) 094 18 41.05096(W) ADJUSTED
AB2800* NAVD 88 -
                        106.36 (meters) 348.9 (feet) GPS OBS
AB2800
                      -404,702.710 (meters)
AB2800 X
                                                            COMP
AB2800 Y
                  - -5,368,084.410 (meters)
                                                            COMP
                 - 3,409,282.244 (meters)
AB2800 Z
                                                            COMP
AB2800 LAPLACE CORR-
                            0.76 (seconds)
                                                           DEFLEC99
AB2800 ELLIP HEIGHT-
                           80.11 (meters)
                                                           GPS OBS
AB2800 GEOID HEIGHT-
                          -26.17 (meters)
                                                            GEOID99
AB2800
AB2800 HORZ ORDER - B
AB2800 ELLP ORDER - FOURTH CLASS II
AB2800. This mark is at Harrison Co (ASL) Airport (ASL)
AB2800. The horizontal coordinates were established by GPS observations
AB2800.and adjusted by the National Geodetic Survey in February 1996.
AB2800. The orthometric height was determined by GPS observations and a
AB2800.high-resolution geoid model.
AB2800
AB2800.GPS derived orthometric heights for airport stations designated as
AB2800.PACS or SACS are published to 2 decimal places. This maintains
AB2800.centimeter relative accuracy between the PACS and SACS. It does
AB2800.not indicate centimeter accuracy relative to other marks which are
AB2800.part of the NAVD 88 network.
AB2800
AB2800. X, Y, and Z were computed from the position and the ellipsoidal ht.
AB2800. The Laplace correction was computed from DEFLEC99 derived deflections.
AB2800. The ellipsoidal height was determined by GPS observations
AB2800.and is referenced to NAD 83.
AB2800. The geoid height was determined by GEOID99.
                   North East Units Scale Converg.
AB2800;
                 - 2,102,524.608 993,403.917 MT 0.99991530 +2 17 04.0
AB2800; SPC TXNC
AB2800;UTM 15 - 3,598,888.117 376,831.251 MT 0.99978707 -0 42 18.4
AB2800
AB2800|-----|
```

```
Distance
AB2800| PID Reference Object
                                                                Geod. Az |
                                                                 dddmmss.s |
AB28001 AB5990 FAA ASL B
                                                  309.174 METERS 01926
AB2800| AB5991 FAA ASL C
                                                  341.990 METERS 12602
AB2800|------
AB2800
AB2800
                                SUPERSEDED SURVEY CONTROL
AB2800
AB2800 ELLIP HT -
                                                             GP( ) 1 1
                               80.17 (m)
AB2800
AB2800. Superseded values are not recommended for survey control.
AB2800.NGS no longer adjusts projects to the NAD 27 or NGVD 29 datums.
AB2800. See file dsdata.txt to determine how the superseded data were derived.
AB2800
AB2800 MARKER: I = METAL ROD
AB2800 SETTING: 59 = STAINLESS STEEL ROD IN SLEEVE (10 FT.+)
AB2800 STAMPING: FAA ASL A 1994
AB2800 PROJECTION: FLUSH
AB2800 MAGNETIC: I = MARKER IS A STEEL ROD
AB2800 STABILITY: B = PROBABLY HOLD POSITION/ELEVATION WELL
AB2800 SATELLITE: THE SITE LOCATION WAS REPORTED AS SUITABLE FOR
AB2800+SATELLITE: SATELLITE OBSERVATIONS - 1994
AB2800 ROD/PIPE-DEPTH: 12.2 meters
AB2800 SLEEVE-DEPTH : 0.90 meters
AB2800
AB2800 HISTORY - Date Condition
AB2800 HISTORY - 1994 MONUMENTED
AB2800 HISTORY - 19980820 GOOD
                                               NGS
                                               TXDOT
AB2800
AB2800
                                STATION DESCRIPTION
AB2800
AB2800'DESCRIBED BY NATIONAL GEODETIC SURVEY 1994 (AJL)
AB2800'THE STATION IS LOCATED ON THE EAST SIDE OF MARSHALL AT THE MARSHALL
AB2800'HARRISON COUNTY AIRPORT, IN THE CENTER OF A GRASS ISLAND CREATED BY
AB2800'THE CIRCLE DRIVE TO THE TERMINAL. OWNERSHIP--HARRISON COUNTY, RT 9
AB2800'BOX 3, MARSHALL, TX 75670. AIRPORT MANAGER IS ROBERT R. AIELLO.
AB2800'PHONE 903-938-1394. CONTACT HIM ONE DAY IN ADVANCE FOR AN ESCORT TO
AB2800'THE STATION. TO REACH FROM THE INTERSECTION OF U.S. HIGHWAYS 80 AND
AB2800'59 IN MARSHALL, GO EAST AND SOUTHEAST ON HIGHWAY 80 FOR 3.13 KM (1.95
AB2800'MI) TO A PAVED ROAD RIGHT (WARREN DRIVE) AND A SIGN NATIONAL GUARD
AB2800'ARMORY-MARSHALL MUNICIPAL AIRPORT. TURN RIGHT, SOUTH, ON WARREN DRIVE
AB2800'FOR 2.39 KM (1.50 MI) TO THE AIRPORT ENTRANCE AND THE STATION ON THE
AB2800'LEFT. STATION IS A PUNCH HOLE TOP CENTER OF A STAINLESS STEEL ROD IN
AB2800'A GREASE FILLED SLEEVE 90 CM LONG ENCASED IN A 12.7 CM PVC PIPE WITH A
AB2800'LOGO CAP SURROUNDED BY CONCRETE SET FLUSH WITH THE GROUND. IT IS 42.4
AB2800'M (139.1 FT) WEST OF THE SOUTH CORNER OF THE TERMINAL, 25.3 M (83.0
AB2800'FT) WEST-NORTHWEST OF A UTILITY POLE WITH TWO TRANSFORMERS, 31.6 M
AB2800'(103.7 FT) EAST-NORTHEAST OF THE CENTER OF WARREN DRIVE, 13.1 M (43.0
AB2800'FT) SOUTH OF A FIRE HYDRANT, 7.5 M (24.6 FT) WEST-SOUTHWEST OF A
AB2800'FLAGPOLE, AND 0.8 M (2.6 FT) WEST OF A FIBERGLASS WITNESS POST.
AB2800'DESCRIBED BY D.G. AUG
AB2800
AB2800
                                STATION RECOVERY (1998)
AB2800'RECOVERY NOTE BY TEXAS DEPARTMENT OF TRANSPORTATION 1998 (WEH)
AB2800'GOOD.
```

(JOHNSON & PACE POINT No. 0117)

NGS STATION FAA F12 A 1994 - RUSK COUNTY AIRPORT


```
National Geodetic Survey, Retrieval Date = MAY 3, 2001
AB2802
*****************
AB2802 PACS - This is a Primary Airport Control Station.
AB2802 DESIGNATION - FAA F12 A 1994
AB2802 PID - AB2802
AB2802 STATE/COUNTY- TX/RUSK
AB2802 USGS QUAD - HENDERSON (1973)
AB2802
AB2802
                             *CURRENT SURVEY CONTROL
AB2802
AB2802* NAD 83(1993) - 32 09 00.12011(N) 094 51 08.20997(W)
                 _
                         130.66 (meters)
AB2802* NAVD 88
                                             428.7 (feet) GPS OBS
AB2802
AB2802 X
                       -457,219.519 (meters)
                                                               COMP
                   - -5,385,939.644 (meters)
AB2802 Y
                                                               COMP
                     3,374,584.252 (meters)
AB2802 Z
                                                               COMP
AB2802 LAPLACE CORR-
                            -0.24 (seconds)
                                                              DEFLEC99
AB2802 ELLIP HEIGHT-
                            104.24 (meters)
                                                              GPS OBS
AB2802 GEOID HEIGHT-
                            -26.31 (meters)
                                                              GEOID99
AB2802
AB2802 HORZ ORDER - B
AB2802 ELLP ORDER - FOURTH CLASS II
AB2802. This mark is at Rusk Co (F12) Airport (F12)
AB2802. The horizontal coordinates were established by GPS observations
AB2802.and adjusted by the National Geodetic Survey in February 1996.
AB2802
AB2802. The orthometric height was determined by GPS observations and a
AB2802.high-resolution geoid model.
AB2802.GPS derived orthometric heights for airport stations designated as
AB2802.PACS or SACS are published to 2 decimal places. This maintains
AB2802.centimeter relative accuracy between the PACS and SACS. It does
AB2802.not indicate centimeter accuracy relative to other marks which are
AB2802.part of the NAVD 88 network.
AB2802
AB2802. X, Y, and Z were computed from the position and the ellipsoidal ht.
AB2802. The Laplace correction was computed from DEFLEC99 derived deflections.
AB2802. The ellipsoidal height was determined by GPS observations
AB2802.and is referenced to NAD 83.
AB2802. The geoid height was determined by GEOID99.
AB2802
AB2802;
                                     East Units Scale Converg.
                         North
                   - 2,059,575.861 944,051.293 MT 0.99999542 +1 59 22.0
AB2802; SPC TXNC
AB2802;UTM 15
                   - 3,558,568.851 325,314.402 MT 0.99997633 -0 59 09.3
AB2802
AB2802:
                     Primary Azimuth Mark
                                                            Grid Az
```

```
AB2802:SPC TXNC - HENPORT AZ MK
                                                           185 12 06.9
AB2802:UTM 15
                 - HENPORT AZ MK
                                                           188 10 38.2
AB2802|------
                                               Distance Geod. Az
AB2802| PID Reference Object
AB2802|
                                                             dddmmss.s |
AB2802| CR1374 HENPORT AZ MK
                                              463.996 METERS 1871128.9 |
AB2802|------
AB2802
                             SUPERSEDED SURVEY CONTROL
AB2802
AB2802 ELLIP HT - 104.29 (m)
                                                      GP( ) 1 1
AB2802. Superseded values are not recommended for survey control.
AB2802.NGS no longer adjusts projects to the NAD 27 or NGVD 29 datums.
AB2802. See file dsdata.txt to determine how the superseded data were derived.
AB2802
AB2802 MARKER: I = METAL ROD
AB2802 SETTING: 59 = STAINLESS STEEL ROD IN SLEEVE (10 FT.+)
AB2802 STAMPING: FAA F12 A 1994
AB2802 PROJECTION: FLUSH
AB2802 MAGNETIC: I = MARKER IS A STEEL ROD
AB2802 STABILITY: B = PROBABLY HOLD POSITION/ELEVATION WELL
AB2802 ROD/PIPE-DEPTH: 6.6 meters
AB2802 SLEEVE-DEPTH : 0.90 meters
AB2802
AB2802 HISTORY - Date Condition Recov. By AB2802 HISTORY - 1994 MONUMENTED NGS
AB2802 HISTORY
                 - 20001226 GOOD
                                            LOCENG
AB2802
                              STATION DESCRIPTION
AB2802'DESCRIBED BY NATIONAL GEODETIC SURVEY 1994 (AJL)
AB2802'THE STATION IS LOCATED ABOUT 3.0 KM (1.85 MI) WEST OF HENDERSON AT THE
AB2802'HENDERSON-RUNK COUNTY AIRPORT, IN BRUSH AT THE NORTH END OF THE
AB2802'AIRFIELD, ALONG THE ENTRANCE ROAD AND ADJACENT TO A CATTLE YARD.
AB2802'OWNERSHIP--RUSK COUNTY, 3355 F.M. 13 WEST, HENDERSON, TX 75652.
AB2802'AIRPORT MANAGER IS J.W. DUNN. PHONE 903-657-7081. TO REACH THE
AB2802'STATION FROM THE JUNCTION OF U.S. HIGHWAYS 79, 259, AND STATE HIGHWAY
AB2802'64 IN HENDERSON, GO WEST ON HIGHWAY 64 FOR 3.47 KM (2.15 MI) TO A
AB2802'CROSSROAD (EVENSIDE ROAD) . TURN LEFT, SOUTH, ON EVENSIDE ROAD FOR
AB2802'2.0 KM (1.25 MI) TO A CROSSROAD. TURN RIGHT, WEST, ON FARM ROAD 13
AB2802'(W. MAIN STREET) FOR 3.30 KM (2.05 MI) TO A Y-JUNCTION. BEAR LEFT,
AB2802'WEST, ON FARM ROAD 13 FOR 0.61 KM (0.35 MI) TO THE AIRPORT ENTRANCE ON
AB2802'THE LEFT. TURN LEFT, SOUTH, ON THE ENTRANCE ROAD FOR 0.01 KM (0.00
AB2802'MI) TO MI) TO THE STATION ON THE RIGHT. THE STATION IS A PUNCH HOLE
AB2802'TOP CENTER OF A STAINLESS STEEL ROD IN A GREAS FILLED SLEEVE ENCASED
AB2802'IN A 12.7 CM PVC PIPE WITH A LOGO CAP SURROUNDED BY CONCRETE SET FLUSH
AB2802'WITH THE GROUND. IT IS 96.7 M (317.3 FT) SOUTH OF THE CENTER OF FARM
AB2802'ROAD 13, 44.4 M (145.7 FT) NORTHWEST OF THE NORTH GATE POST OF A GATE
AB2802'IN A PIPE FENCE, 26.5 M (86.9 FT) WEST OF AND ACROSS THE ROAD FROM THE
AB2802'PIPE FENCE, 16.6 M (54.5 FT) WEST OF THE CENTER OF THE ENTRANCE ROAD,
AB2802'AND 0.8 M (2.6 FT) EAST OF A FIBERGLASS WITNESS POST. DESCRIBED BY
AB2802'D.G. AUG
```

NGS STATION E 160 – GREGG COUNTY COURTHOUSE

```
National Geodetic Survey, Retrieval Date = MAY 3, 2001
CR0161
****************
CR0161 DESIGNATION - E 160
CR0161 PID - CR0161
CR0161 STATE/COUNTY- TX/GREGG
CR0161 USGS QUAD - LAKEPORT (1983)
CR0161
CR0161
                             *CURRENT SURVEY CONTROL
CR0161
CR0161* NAD 83(1986) - 32 29 47.
                                 (N) 094 44 19.
                                                      (W)
                                                              SCALED
CR0161* NAVD 88 -
                         108.303 (meters) 355.32 (feet) ADJUSTED
CR0161
CR0161 GEOID HEIGHT-
                           -26.31 (meters)
                       108.178 (meters) 354.91 (feet) COMP
CR0161 DYNAMIC HT -
CR0161 MODELED GRAV- 979,491.1 (mgal)
                                                              NAVD 88
CR0161
CR0161 VERT ORDER - SECOND CLASS 0
CR0161. The horizontal coordinates were scaled from a topographic map and have
CR0161.an estimated accuracy of \pm 6 seconds.
CR0161
CR0161. The orthometric height was determined by differential leveling
CR0161.and adjusted by the National Geodetic Survey in June 1991.
CR0161
CR0161. The geoid height was determined by GEOID99.
CR0161
CR0161. The dynamic height is computed by dividing the NAVD 88
CR0161.geopotential number by the normal gravity value computed on the
CR0161. Geodetic Reference System of 1980 (GRS 80) ellipsoid at 45
CR0161.degrees latitude (g = 980.6199 \text{ gals.}).
CR0161
CR0161. The modeled gravity was interpolated from observed gravity values.
CR0161
CR0161;
                         North
                                    East Units Estimated Accuracy
CR0161; SPC TXNC -2,098,340. 953,390. MT (+/- 180 meters Scaled)
CR0161
CR0161
                             SUPERSEDED SURVEY CONTROL
CR0161
CR0161 NGVD 29 - 108.333 (m) 355.42 (f) ADJ UNCH 2 0
CR0161. Superseded values are not recommended for survey control.
CR0161.NGS no longer adjusts projects to the NAD 27 or NGVD 29 datums.
CR0161. See file dsdata.txt to determine how the superseded data were derived.
CR0161
CR0161 MARKER: DB = BENCH MARK DISK
CR0161 SETTING: 7 = SET IN TOP OF CONCRETE MONUMENT
CR0161 STAMPING: E 160 1934
CR0161 STABILITY: C = MAY HOLD, BUT OF TYPE COMMONLY SUBJECT TO
CR0161+STABILITY: SURFACE MOTION
CR0161
```

```
CR0161 HISTORY - Date Condition
                                            Recov. By
CR0161 HISTORY
                 - 1934
                            MONUMENTED
                                             CGS
CR0161 HISTORY
                 - 1972
                             GOOD
                                             LOCENG
CR0161
CR0161
                              STATION DESCRIPTION
CR0161
CR0161'DESCRIBED BY COAST AND GEODETIC SURVEY 1934
CR0161'IN LONGVIEW.
CR0161'GREGG COUNTY COURT HOUSE GROUNDS. AT SOUTH SIDE FACING METHVIN
CR0161'STREET. IN CENTER OF WEST END OF LAWN STRIP BETWEEN CONCRETE WALKS TO
CR0161'MAIN ENTRANCE OF BUILDING. TABLET SET IN TOP OF CONCRETE POST, 50
CR0161'YARDS FROM C.L. OF METHVIN STREET.
CR0161
CR0161
                              STATION RECOVERY (1972)
CR0161
CR0161'RECOVERY NOTE BY LOCAL ENGINEER (INDIVIDUAL OR FIRM) 1972
CR0161'RECOVERED IN GOOD CONDITION.
```



PRIMARY CONTROL GEODETIC POSITIONS

Horizontal Coordinate System: State Plane Coordinate 1983 Date: 03/30/02

Height System: Ortho. Ht. (GEOID99) Desired Horizontal Accuracy: 0.033USft + 10ppm Desired Vertical Accuracy: 0.066USft + 10ppm Confidence Level: 95% Err.

Linear Units of Measure: US Feet

	Site ID	Site Descriptor			Positio	n	95% Error	Fix Status
1	0105	FAA GGG A	Lat. Lon. Elv.		35.35432" 10.17601" 355.900		0.000 0.000 0.000	Fixed Fixed Fixed
2	0115	DARBY 1	Lat. Lon. Elv.		54.03601" 20.22741" 354.699		0.043 0.057 0.081	
3	0110	DARCO	Lat. Lon. Elv.		46.32191" 06.30411" 360.831		0.050 0.068 0.089	
4	1211	HALLSVILLE	Lat. Lon. Elv.		38.86848" 34.14521" 396.268		0.040 0.052 0.069	
5	0109	TATUM	Lat. Lon. Elv.		40.45161" 19.99111" 353.421		0.051 0.067 0.093	
6	0104	GLOX	Lat. Lon. Elv.		27.12568" 01.40252" 384.039		0.035 0.042 0.052	
7	0103	4F4 A 1994	Lat. Lon. Elv.		11.99241" 54.90254" 413.500		0.000 0.000 0.000	Fixed Fixed Fixed
8	0101	FAA 07F A 1994	Lat. Lon. Elv.		34.13033" 56.79070" 286.900		0.000 0.000 0.000	Fixed Fixed Fixed
9	0102	CHARLIE BROWN	Lat. Lon. Elv.		04.58408" 28.55638" 412.945		0.040 0.050 0.067	
10	0113	KILGORE	Lat. Lon. Elv.		08.93138" 09.36126" 355.158		0.041 0.054 0.071	

	Site ID	Site Descriptor			Position	95% Error	Fix Status
11	0114	CRIM	Lat. Lon. Elv.		36.52259" N 43.97371" W 388.427	0.056 0.068 0.090	
12	0116	SH 43 / TUMCO	Lat. Lon. Elv.		16.68848" N 56.58879" W 439.554	0.059 0.071 0.095	
13	0117	FAA F12 A 1994	Lat. Lon. Elv.	32° 09' 94° 51'	00.12012" N 08.20997" W 428.700	0.000 0.000 0.000	Fixed Fixed Fixed
14	0111	NESBITT	Lat. Lon. Elv.		25.75804" N 45.37249" W 331.450	0.050 0.069 0.098	
15	0112	FAA ASL A 1994	Lat. Lon. Elv.		13.75733" N 41.05096" W 348.900	0.000 0.000 0.000	Fixed Fixed Fixed
16	0108	HARLETON	Lat. Lon. Elv.	32° 40' 94° 35'	43.41252" N 02.25408" W 349.954	0.071 0.092 0.133	

PRIMARY CONTROL GRID POSITIONS

Horizontal Coordinate System: State Plane Coordinate 1983 Date: 03/30/02

Height System: Ortho. Ht. (GEOID99) Desired Horizontal Accuracy: 0.033USft + 10ppm Desired Vertical Accuracy: 0.066USft + 10ppm Confidence Level: 95% Err.


Linear Units of Measure: US Feet


	Site ID	Site Descriptor		Position	95% Error	Fix Status
1	0105	FAA GGG A	East. Nrth. Elev.	3140306.953 6847154.379 355.900	0.000 0.000 0.000	Fixed Fixed Fixed
2	0115	DARBY 1	East. Nrth. Elev.	3131620.842 6921537.634 354.699	0.057 0.043 0.081	
3	0110	DARCO	East. Nrth. Elev.	3217241.761 6863272.724 360.831	0.068 0.050 0.089	
4	1211	HALLSVILLE	East. Nrth. Elev.	3167514.611 6890977.533 396.268	0.052 0.040 0.069	
5	0109	TATUM	East. Nrth. Elev.	3191770.257 6825301.010 353.421	0.067 0.051 0.093	
6	0104	GLOX	East. Nrth. Elev.	3108746.553 6887666.167 384.039	0.042 0.035 0.052	
7	0103	4F4 A 1994	East. Nrth. Elev.	3060682.172 6957280.049 413.500	0.000 0.000 0.000	Fixed Fixed Fixed
8	0101	FAA 07F A 1994	East. Nrth. Elev.	3057565.447 6892678.558 286.900	0.000 0.000 0.000	Fixed Fixed Fixed
9	0102	CHARLIE BROWN	East. Nrth. Elev.	3094754.808 6927366.026 412.945	0.050 0.040 0.067	
10	0113	KILGORE	East. Nrth. Elev.	3088847.169 6848729.651 355.158	0.054 0.041 0.071	

	Site ID	Site Descriptor		Position	95% Error	Fix Status
11	0114	CRIM	East. Nrth. Elev.	3108049.314 6803652.317 388.427	0.068 0.056 0.090	
12	0116	SH 43 / TUMCO	East. Nrth. Elev.	3143732.716 6784717.264 439.554	0.071 0.059 0.095	
13	0117	FAA F12 A 1994	East. Nrth. Elev.	3097274.950 6757125.137 428.700	0.000 0.000 0.000	Fixed Fixed Fixed
14	0111	NESBITT	East. Nrth. Elev.	3216775.281 6921853.608 331.450	0.069 0.050 0.098	
15	0112	FAA ASL A 1994	East. Nrth. Elev.	3259192.683 6898032.819 348.900	0.000 0.000 0.000	Fixed Fixed Fixed
16	0108	HARLETON	East. Nrth. Elev.	3173100.810 6952320.035 349.954	0.092 0.071 0.133	

	Site ID	Site Descriptor	Convergence	Scale Factor
1	0105	FAA GGG A	2° 04.257′	0.99993818
2	0115	DARBY 1	2° 03.621′	0.99990371
3	0110	DARCO	2° 12.474′	0.99993114
4	1211	HALLSVILLE	2° 07.312′	0.99991687
5	0109	MUTAT	2° 09.622′	0.99995180
6	0104	GLOX	2° 01.065′	0.99991740
7	0103	4F4 A 1994	1° 56.215′	0.99989098
8	0101	FAA 07F A 1994	1° 55.653′	0.99991439

	Site ID	Site Descriptor	Convergence	Scale Factor
9	0102	CHARLIE BROWN	1° 59.727′	0.99990108
10	0113	KILGORE	1° 58.811′	0.99993634
11	0114	CRIM	2° 00.678′	0.99996335
12	0116	SH 43 / TUMCO	2° 04.381′	0.99997680
13	0117	FAA F12 A 1994	1° 59.367′	0.99999542
14	0111	NESBITT	2° 12.664′	0.99990480
15	0112	FAA ASL A 1994	2° 17.066′	0.99991530
16	0108	HARLETON	2° 08.147′	0.99989367





ETJ CONTROL GEODETIC POSITIONS

Horizontal Coordinate System: State Plane Coordinate 1983 Date: 03/30/02

Height System: Ortho. Ht. (GEOID99)
Desired Horizontal Accuracy: 0.033USft + 10ppm

Desired Horizontal Accuracy: 0.033USft + 10ppm
Desired Vertical Accuracy: 0.066USft + 10ppm

Confidence Level: 95% Err. Linear Units of Measure: US Feet

	Site ID	Site Descriptor			Position	95% Error	Fix Status
1	1204	McCANN/PLILER	Lat. Lon. Elv.		12.58712" N 25.04225" W 399.481	0.008 0.011 0.017	
2	1201	MACKEY RD	Lat. Lon. Elv.		33.92731" N 36.14935" W 368.879	0.013 0.018 0.026	
3	1202	FM 449	Lat. Lon. Elv.		46.99707" N 43.78804" W 432.906	0.009 0.012 0.019	
4	1205	KAWASAKI	Lat. Lon. Elv.		12.55134" N 04.45884" W 397.596	0.008 0.011 0.016	
5	1227	WHITE OAK ROAD	Lat. Lon. Elv.		12.46089" N 27.98452" W 446.428	0.013 0.018 0.027	
6	1203	US259/JUDSON	Lat. Lon. Elv.		16.07526" N 14.74191" W 401.175	0.009 0.012 0.018	
7	0102	SH300/FM3358	Lat. Lon. Elv.		04.58408" N 28.55638" W 412.945	0.000 0.000 0.000	Fixed Fixed Fixed
8	0115	DARBY 1	Lat. Lon. Elv.		54.03601" N 20.22740" W 354.699	0.000 0.000 0.000	Fixed Fixed Fixed
9	1208	MALL/TUTTLE	Lat. Lon. Elv.	32° 94°	29.99250" N 02.88229" W 349.735	0.008 0.011 0.015	
10	1207	SH300/FM1844	Lat. Lon. Elv.		27.90371" N 11.33388" W 435.813	0.010 0.015 0.021	

S	ite ID	Site Descriptor		Position	95% Error	Fix Status
11	1229	FM2275/FM1845	Lat. Lon. Elv.	23.75759" N 53.20630" W 400.177	0.012 0.015 0.022	
12	1224	US80/MOSLEY	Lat. Lon. Elv.	17.66218" N 30.94283" W 324.057	0.008 0.009 0.013	
13	1228	LONGVIEW CC	Lat. Lon. Elv.	23.56919" N 02.24264" W 319.363	0.012 0.016 0.024	
14	0104	US80/GLOX	Lat. Lon. Elv.	27.12568" N 01.40252" W 384.039	0.000 0.000 0.000	Fixed Fixed Fixed
15	1226	SH300/BLUE RIDGE	Lat. Lon. Elv.	20.91928" N 28.85916" W 412.821	0.008 0.011 0.015	
16	1230	WHATLEY/ROCKIN B	Lat. Lon. Elv.	29.65821" N 08.41282" W 351.908	0.010 0.014 0.021	
17	1225	B OWENS/MOSLEY	Lat. Lon. Elv.	26.81491" N 48.32713" W 326.050	0.008 0.010 0.014	
18	1221	SH 31	Lat. Lon. Elv.	12.85681" N 11.30255" W 264.313	0.013 0.017 0.025	
19	1222	FM1845/MICHAEL	Lat. Lon. Elv.	53.60766" N 18.69102" W 266.395	0.010 0.012 0.018	
20	1212	LOOP 281	Lat. Lon. Elv.	01.03142" N 58.87510" W 373.189	0.009 0.012 0.017	
21	1223	SH31/FM1845	Lat. Lon. Elv.	44.49735" N 04.39269" W 328.082	0.011 0.014 0.021	
22	1213	WELLNESS	Lat. Lon. Elv.	12.32531" N 28.53056" W 378.036	0.009 0.012 0.017	
23	1200	CITY HALL	Lat. Lon. Elv.	43.83841" N 44.30433" W 318.762	0.009 0.012 0.017	

Sit	e ID	Site Descriptor			Position		Fix Status
24	1209	FM2208/FM2879	Lat. Lon. Elv.		21.11573" N 02.02524" W 411.924		
25	1214	EASTMAN/COTTON	Lat. Lon. Elv.		30.93235" N 26.01335" W 342.412		
26	1211	HALLSVILLE	Lat. Lon. Elv.		38.86848" N 34.14521" W 396.268		Fixed Fixed Fixed
27	1218	TX EASTMAN CO	Lat. Lon. Elv.		08.72995" N 09.36874" W 288.851		
28	1210	US80/TRINITY	Lat. Lon. Elv.		14.44539" N 58.10826" W 340.412		
29	1217	TALLEY ROAD	Lat. Lon. Elv.		42.06838" N 44.93661" W 264.400		
30	1216	NEIMAN MARCUS	Lat. Lon. Elv.		46.33039" N 17.62337" W 330.911		
31	1206	FM 2879	Lat. Lon. Elv.		35.06971" N 17.53087" W 387.657		
32	1215	IH 20/LANSING	Lat. Lon. Elv.		01.15751" N 04.91978" W 340.837		
33	0105	GGGA	Lat. Lon. Elv.	32° 23′ 94° 42′	35.35432" N 10.17601" W 355.900	0.000 0.000 0.000	Fixed Fixed Fixed
34	1219	SH149/SH322	Lat. Lon. Elv.		53.53909" N 26.35913" W 264.157		
35	1220	IH 20/SABINE R	Lat. Lon. Elv.		54.09473" N 08.15537" W 277.604		
36	0132	JAIL	Lat. Lon. Elv.		52.25912" N 21.14304" W 375.102		

ETJ CONTROL GRID POSITIONS

Horizontal Coordinate System: State Plane Coordinate 1983 Date: 03/30/02

Height System: Ortho. Ht. (GEOID99)
Desired Horizontal Accuracy: 0.033USft + 10ppm

Desired Horizontal Accuracy: 0.033USft + 10ppm
Desired Vertical Accuracy: 0.066USft + 10ppm

Confidence Level: 95% Err. Linear Units of Measure: US Feet

	Site ID	Site Descriptor		Position	95% Error	Fix Status
1	1204	McCANN/PLILER	East. Nrth. Elev.	3116184.797 6910727.563 399.481	0.011 0.008 0.017	
2	1201	MACKEY RD	East. Nrth. Elev.	3109386.188 6930846.268 368.879	0.018 0.013 0.026	
3	1202	FM 449	East. Nrth. Elev.	3129414.602 6926813.809 432.906	0.012 0.009 0.019	
4	1205	KAWASAKI	East. Nrth. Elev.	3128207.082 6911152.806 397.596	0.011 0.008 0.016	
5	1227	WHITE OAK ROAD	East. Nrth. Elev.	3085147.076 6909628.306 446.428	0.018 0.013 0.027	
6	1203	US259/JUDSON	East. Nrth. Elev.	3121751.758 6923412.708 401.175	0.012 0.009 0.018	
7	0102	SH300/FM3538	East. Nrth. Elev.	3094754.808 6927366.026 412.945	0.000 0.000 0.000	Fixed Fixed Fixed
8	0115	DARBY 1	East. Nrth. Elev.	3131620.843 6921537.634 354.699	0.000 0.000 0.000	Fixed Fixed Fixed
9	1208	MALL/TUTTLE	East. Nrth. Elev.	3123580.752 6900616.487 349.735	0.011 0.008 0.015	
10	1207	SH300/FM1844	East. Nrth. Elev.	3101697.394 6917832.555 435.813	0.015 0.010 0.021	

	Site ID	Site Descriptor		Position	95% Fix Error Status
11	1229	FM2275/FM1845	East. Nrth. Elev.	3098555.396 6905169.266 400.177	0.015 0.012 0.022
12	1224	US80/MOSLEY	East. Nrth. Elev.	3116521.754 6886984.087 324.057	0.009 0.008 0.013
13	1228	LONGVIEW CC	East. Nrth. Elev.	3093493.608 6880705.769 319.363	0.016 0.012 0.024
14	0104	US80/GLOX	East. Nrth. Elev.	3108746.553 6887666.167 384.039	0.000 Fixed 0.000 Fixed 0.000 Fixed
15	1226	SH300/BLUE RIDGE	East. Nrth. Elev.	3111125.660 6899256.725 412.821	0.011 0.008 0.015
16	1230	WHATLEY/ROCKIN B	East. Nrth. Elev.	3097656.863 6893600.480 351.908	0.014 0.010 0.021
17	1225	B OWENS/MOSLEY	East. Nrth. Elev.	3119920.270 6894097.508 326.050	0.010 0.008 0.014
18	1221	SH 31	East. Nrth. Elev.	3108590.040 6868016.510 264.313	0.017 0.013 0.025
19	1222	FM1845/MICHAEL	East. Nrth. Elev.	3123223.824 6872655.723 266.395	0.012 0.010 0.018
20	1212	LOOP 281	East. Nrth. Elev.	3144780.300 6892384.382 373.189	0.012 0.009 0.017
21	1223	SH31/FM1845	East. Nrth. Elev.	3119128.298 6877655.867 328.082	0.014 0.011 0.021
22	1213	WELLNESS	East. Nrth. Elev.	3132151.752 6887002.599 378.036	0.012 0.009 0.017
23	1200	CITY HALL	East. Nrth. Elev.	3125769.908 6883893.178 318.762	0.012 0.009 0.017

	Site ID	Site Descriptor		Position	95% Error	Fix Status
24	1209	FM2208/FM2879	East. Nrth. Elev.	3139084.195 6900276.100 411.924	0.012 0.009 0.018	
25	1214	EASTMAN/COTTON	East. Nrth. Elev.	3137652.912 6883015.131 342.412	0.012 0.009 0.017	
26	1211	HALLSVILLE	East. Nrth. Elev.	3167514.611 6890977.533 396.268	0.000	Fixed Fixed Fixed
27	1218	TX EASTMAN CO	East. Nrth. Elev.	3139815.983 6862646.259 288.851	0.012 0.009 0.016	
28	1210	US80/TRINITY	East. Nrth. Elev.	3155286.198 6888057.028 340.412	0.013 0.009 0.018	
29	1217	TALLEY ROAD	East. Nrth. Elev.	3157422.996 6860591.651 264.400	0.019 0.014 0.028	
30	1216	NEIMAN MARCUS	East. Nrth. Elev.	3143889.853 6872663.417 330.911	0.013 0.010 0.019	
31	1206	FM 2879	East. Nrth. Elev.	3142179.410 6920001.292 387.657	0.018 0.013 0.025	
32	1215	IH 20/LANSING	East. Nrth. Elev.	3165470.053 6874953.365 340.837	0.019 0.013 0.028	
33	0105	GGGA	East. Nrth. Elev.	3140306.953 6847154.379 355.900	0.000	Fixed Fixed Fixed
34	1219	SH149/SH322	East. Nrth. Elev.	3138635.122 6855000.148 264.157	0.012 0.009 0.017	
35	1220	IH 20/SABINE R	East. Nrth. Elev.	3119417.655 6860435.120 277.604	0.019 0.014 0.026	
36	0132	JAIL	East. Nrth. Elev.	3127721.770 6884814.528 375.102	0.014 0.012 0.023	

	Site ID	Site Descriptor	Convergence	Scale Factor
1	1204	McCANN/PLILER	2° 01.941	' 0.99990769
2	1201	MACKEYRD	2° 01.294	0.99990002
3	1202	FM 449	2° 03.407	' 0.99990173
4	1205	KAWASAKI	2° 03.219	' 0.99990769
5	1227	WHITE OAK ROAD	1° 58.642	' 0.99990770
6	1203	US259/JUDSON	2° 02.580	' 0.99990288
7	0102	SH300/FM3538	1° 59.727	0.99990108
8	0115	DARBY 1	2° 03.621	' 0.99990371
9	1208	MALL/TUTTLE	2° 02.688	0.99991196
10	1207	SH300/FM1844	2° 00.429	0.99990471
11	1229	FM2275/FM1845	2° 00.049	' 0.99990970
12	1224	US80/MOSLEY	2° 01.887	' 0.99991783
13	1228	LONGVIEW CC	1° 59.421	' 0.99992035
14	0104	US80/GLOX	2° 01.065	' 0.99991740
15	1226	SH300/BLUE RIDGE	2° 01.361	' 0.99991235
16	1230	WHATLEY/ROCKIN B	1° 59.910	0.99991459
17	1225	B OWENS/MOSLEY	2° 02.274	0.99991472
18	1221	SH 31	2° 00.975	0.99992671
19	1222	FM1845/MICHAEL	2° 02.544	0.99992469
20	1212	LOOP 281	2° 04.906	' 0.99991586
21	1223	SH31/FM1845	2° 02.128	' 0.99992221
22	1213	WELLNESS	2° 03.545	0.99991808
23	1200	CITY HALL	2° 02.856	0.99991940
24	1209	FM2208/FM2879	2° 04.332	0.99991234
25	1214	EASTMAN/COTTON	2° 04.113	0.99992000
26	1211	HALLSVILLE	2° 07.312	0.99991687

	Site ID	Site Descriptor	Convergence	Scale Factor
27	1218	TX EASTMAN CO	2° 04.265′	0.99992998
28	1210	US80/TRINITY	2° 06.003′	0.99991798
29	1217	TALLEY ROAD	2° 06.123′	0.99993136
30	1216	NEIMAN MARCUS	2° 04.735′	0.99992505
31	1206	FM 2879	2° 04.736′	0.99990444
32	1215	IH 20/LANSING	2° 07.032′	0.99992432
33	0105	GGGA	2° 04.257′	0.99993818
34	1219	SH149/SH322	2° 04.110′	0.99993393
35	1220	IH 20/SABINE R	2° 02.094′	0.99993074
36	0132	JAIL	2° 03.067′	0.99991901



PSM 0101 FAA 07F A 1994, GLADEWATER AIRPORT



PSM 0102 (CHARLIE BROWN) SH 300 & FM 3358




PSM 0103 4F4 A 1994, GILMER AIRPORT



PSM 0104 (GLOX)
AMERICAN MAID CLEANING COMPANY (FORMERLY GLO)



PSM 0105 (GGG A)
FAA GGG A @ GREGG COUNTY AIRPORT



0105 (GGG A)



PSM 0108 (HARLETON)



PSM 0109 (TATUM)



PSM 110 (DARCO)



PSM 0111 (NESBITT)



PSM 0112 (FAA ASL A 1994) MARSHALL AIRPORT



PSM 0113 (KILGORE)



PSM 0114 (CRIM)



PSM 0115 (DARBY 1)ON PRIVATE PROPERTY, SEE BAR-K LAND COMPANY



PSM 0116 (SH 43 / TUMCO)
TUMCO RR BRIDGE IN BACKGROUND



PSM 0117 (FAA F12 A 1994) HENDERSON AIRPORT



PSM 0304 INDUSTRIAL STEEL, 4750 WEST MARSHALL AVENUE





CSM 1200 AT CITY HALL



CSM 1300



CSM 1201



CSM 1301



CSM 1202



CSM 1302



CSM 1203



CSM 1303



CSM 1204



CSM 1304




CSM 1205



CSM 1305



CSM 1206



CSM 1306



CSM 1207



CSM 1307



CSM 1208



CSM 1308



CSM 1209



CSM 1309



CSM 1210



CSM 1310



CSM 1211



CSM 1311



CSM 1212



CSM 1312



CSM 1213




CSM 1313



CSM 1214



CSM 1314



CSM 1215



CSM 1315



CSM 1216



CSM 1316



CSM 1217



CSM 1317



CSM 1218



CSM 1318



CSM 1219



CSM 1319





CSM 1220



CSM 1320



CSM 1221



CSM 1321





CSM 1222



CSM 1322



CSM 1223



CSM 1323



CSM 1224



CSM 1324



CSM 1225



CSM 1325



CSM 1226



CSM 1326



CSM 1227



CSM 1327



CSM 1228



CSM 1328



CSM 1229



CSM 1329




CSM 1230



CSM 1330

PACE SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

Marker is located at the intersection of State Highway 300 amd FM 3358, north of Longview and north of FM 1844, on the north east corner of the intersection.

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II — TEXAS PLS 1573" and field stamped "0102".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 094, 754.808 6, 927, 366.026 Lat. 32° 37′ 04.58408″ N Lon. 94° 50′ 28.55638″ W

Elv.

412.95

Convergence Scale Factor 1°59.727°0.99990108

JOHNSON & PACE CONTROL

PSM 0102

johnson & pace engineering & surveying consultants -- job no. 1994-001 -- april 2002

PACE SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK American Maid Cleaning Company PSM 0104 BC BC BC BC SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK

WEST MARSHALL AVE, (US 80)

GENERAL LOCATION:

In front of American Maid Cleaning Company (formerly GLO Company) at 4105 West Marshall Avenue.

Mark is an "X" chiseled in a concret driveway.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 108, 746.553 Lat. 32° 30 27.12568 North. 6, 887, 666.167 Lon. 94° 48 01.40252 W

Elev. 384.04

Convergence 2° 01.065' PSM 0104 (GLOX)
Scale Factor 0.99991740 JOHNSON & PACE CONTROL


PACE SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW

2002 HORIZONTAL & VERTICAL CONTROL NETWORK



HOUSE #4721

US HIGHWAY 80



GENERAL LOCATION:

Marker is located on US Highway 80 west of Loop 281 West, and east of Silverfalls Road. An X cut in the concrete drive way of Industrial Steel, across the street from house #4721

Mark is an "X" chiseled in a concret driveway.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North.

3, 106, 400.865 6, 887, 894, 657

32°30 Lat. 30.20175 94 ° 48 Lon. 28.68489

Elev.

402.07


Convergence


2 · 00.817 PSM 0304 (AZM FOR GLOX)

Scale Factor

0.99991726

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK





GENERAL LOCATION:

Marker is located on the south side of State Highway No. 154 approximately 0.3 mile southwest of the intersection of SH 154 and FM 450

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II — TEXAS PLS 1573" and field stamped "0108".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA F12 A 1994". "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 173, 100.810 6, 952, 320.035

32° 40' 43.41252" N Lat. 94° 35' 02.25408" W Lon.

Elev.


349.954

Convergence

2° 08.147' PSM 0108 (HARLETON)

Scale Factor

0.99989367



GENERAL LOCATION:

Marker is located 10.9 miles south of Lake Port on SH 149 and 2.4 miles northwest of Tatum, on the north side of the road in front of the Masonic Lodge.

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II — TEXAS PLS 1573" and field stamped "0109".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of \pm 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 191, 770.257 North. 6, 825, 301.010 Elev. 353.421

..257 Lat. 32°19'40.45161" N ..010 Lon. 94°32'19.99111" W


Convergence 2° 09.622'

PSM 0109 (TATUM)

Scale Factor

0.99995180

PACE SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

Marker on FM 2625 west of SH 43 approximately 1 mile, and east of FM 3251 approximately .75 mile, on the south side of the road.

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II — TEXAS PLS 1573" and field stamped "963".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of \pm 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 217, 241, 761 6, 863, 272, 724 Lat. 32° 25' 46.32191" N Lon. 94° 27' 06.30411" W

Elev.

360.83

Convergence

2° 12.474'

PSM 0110 (DARCO)

Scale Factor

0.99993114

PACE SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK CENTER HILL ROAD ÑTS STATE HICHWAYNO. 159 PSM 0111 DRIVEWAY RED SIMPSON, INC.

GENERAL LOCATION:

Marker is located on the south side of State Highway No. 154 approximately 74' from the front entrance of Red Simpson Inc.

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II – TEXAS PLS 1573" and field stamped "0111".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 216, 775.281 32° 35' 25.75804" N 94° 26' 45.37249" W North. 6, 921, 853.608 Lon.

Elev. 331.45


Convergence 2°12.66' Scale Factor

PSM 0111 (NESBITT)

JOHNSON & PACE CONTROL

0.99990480

PACE SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

Marker is located at the intersectio of State Highway 42 and State Highway 31. on the northwest corner.

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II — TEXAS PLS 1573" and field stamped "0113".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:


East. 3, 088, 847.169 North. 6, 848, 729.651

Lat. 32°24′08.93138″N Lon. 94°52′09.36126″W

Elev. 355.16

PSM 0113 (KILGORE)

Convergence 1° 58.811'
Scale Factor 0.99993634



GENERAL LOCATION:

Marker is located at the intersection of FM 850 and FM 2276

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II — TEXAS PLS 1573" and field stamped "0114".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', "FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of \pm 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 108, 049.314 North. 6, 803, 652.317

Lat. 32° 16′ 36.52259″ N Lon. 94° 48′ 43.97371″ W

Elev. 388.43 *Convergence* 2° 00.678'

JOHNSON & PACE CONTROL

PSM 0114 (CRIM)

Scale Factor 0.99996335

PACE SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK ASPHALT CIRCLE DRIVE GATE POST DIAT DRIVE OR METER OR METER

GENERAL LOCATION:

Marker is located in the Bar Chase Development off of Bar-K-Ranch Road. At the intersection of Bar Chase Trail and Water Chase Court take the private drive on the north side of the road, go through gate bearing to the right to a gate in a wood fence, see map.

LOCATED ON PRIVATE PROPERTY: CONTACT BAR-K LAND COMPANY 3583 SAM PAGE ROAD - 903-663-6363

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II – TEXAS PLS 1573" and field stamped "0115".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:


East. 3, 131, 620.842 Lat. 32° 35′ 54.03601″ N North. 6, 921, 537.634 Lon. 94° 43′ 20.22741″ W

Elev. 354.70

Convergence 2° 03.621' PSM 0115 (DARBY 1)

Scale Factor 0.99990371 JOHN





GENERAL LOCATION:

Marker is located on the east side of SH 43 near an asphalt drive to a pasture, approximately 400' north of a Rail Road Overpass.

Mark is a 5/8" iron rod placed in concrete with a 2" aliminum cap imprinted "LONNIE C. PACE, II — TEXAS PLS 1573" and field stamped "0116".

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 143, 732.716 6, 784, 717.264 Lat. 32° 13′ 16.68848″ N Lon. 94° 41′ 56.58879″ W

Elev.

439.55


Convergence

2 04.381

Scale Factor 0.99997680

PSM 0116 (SH43/TUMCO)

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is on the grounds at City Hall, south of the curb on Cotton Street and north of the curb on the City parking lot

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:


East. 3, 125, 769.908 Lat. 32° 29' 43.83841" N North. 6, 883, 893.178 Lon. 94° 44' 44.30433" W

Elev. 318.76

Convergence 2° 02.856

Scale Factor 0.99991940

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is on the north side of Cotton Street, approximately 1150 feet westerly from City Hall.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of $\pm/-$ 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 124, 568.728 North. 6, 884, 072.992

Lat. 32°29′46.04110″N Lon. 94°44′58.24598″W

Elev. 295.82

CSM 1300
AZIMUTH MARKER FOR CSM 1200

Convergence 2° 02.730° Scale Factor 0.99991930

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK NTS MARTIN MACKEY ROAD APPROXIMATELY 600'

GENERAL LOCATION:

The marker is on the north side of Martin Road approximately one mile southerly from the intersection with Mackey Road.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. Nrth. 3, 109, 386. 188° 6, 930, 846. 268 Lat. 32° 37′ 33.92731″ N Lon. 94° 47′ 36.14935″ W

Elev.

368.88

Convergence


2°01.294

Scale Factor

0.99990002

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK





GENERAL LOCATION:

The marker is on the north side of Martin Road approximately 1-1/2 mile southerly from the intersection with Mackey Road.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 107, 381.309 6, 929, 997.076 Lat. 32° 37′ 26.22855″ N Lon. 94° 47′ 59.92876″ W

Elev.

375.30

Convergence


2° 01.078'

Scale Factor

0.99990030

CSM 1301 AZIMUTH MARKER FOR CSM 1201

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



HUNTER ROAD +/- 600'

SAM PAGE ROAD +/- 2800′

GENERAL LOCATION:

The marker is located north of Longview on FM 449, east of US Highway 259 and .5 mile from Sam Page Road, and north of the pavement

Marker is a 5/8" x 5' repar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS -2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North 3, 129, 414.602 6, 926, 813.809

Lat. 32° 36′ 46.99707″ N Lon. 94° 43′ 43.78804″ W

Elev.


432.91

Convergence

2°03.407

Scale Factor

0.99990173



GENERAL LOCATION:

The marker is on the north side of F. M. 449 approximately 1600' west of Hunter's Road and approximately 2300' east of F. M. 2571.

Marker is a 5/8" x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

Convergence

GEODETIC POSITION:

East. 3. 127, 434.464 North. 6, 927, 894.345

Lat. 32°36′58.38532″N Lon. 94°44′06.47209″W

Elev. 417.62

2°03.200'

Scale Factor 0.99990131

CSM 1302 AZIMUTH MARKER FOR CSM 1202

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK BASE OF SIGN OVERHEAD SIGN OST NOS CSM 1203 SERVE SO VERTICAL CONTROL NETWORK SERVE SO VERTICAL CONTROL NETWORK OVERHEAD SIGN OST NOS VERTICAL CONTROL NETWORK SO VERTICAL CONTROL NETWORK OST NOS VERTICAL CONTRO

GENERAL LOCATION:

The marker is located east of the intersection of Spur 502 (Judson Road) and US Highway 259, just south of Hamby Road.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:


East. 3, 121, 751.758 North. 6, 923, 412.708

Lat. 32° 36′ 16.07526″ N Lon. 94° 45′ 14.74191″ W

Elev. 401.18 Convergence 2° 02.580

Scale Factor 0.99990288

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is located in the center median of US Highway 259, approximately .25 mile north of FM 2751.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of \pm 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 124, 338.015 North. 6, 919, 456.827

Lat. 32° 35′ 36.04133″ N Lon. 94° 44′ 46.17805″ W

Elev. 432.53


CSM 1303

 Convergence
 2° 02.839°

 Scale Factor
 0.99990440

AZIMUTH MARKER FOR CSM 1203

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is on McCann Road north of Pliler Precise Road, on the west side of the street, across the street from the pond.

Marker is a 5/8" x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:


GEODETIC POSITION:

East. 3, 116, 184.797 North. 6, 910, 727.563

Lat. 32°34′12.58712″N Lon. 94°46′25.04225″W

Elev. 399.48 Convergence 2°01.941'

Scale Factor 0.99990769



GENERAL LOCATION:

The marker is located north of Spring Hill Road on McCann Road, and north of Greystone, opn the east side of the street.

Marker is a $5/8\,^\circ$ x $5\,^\circ$ rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

Scale Factor

GEODETIC POSITION:

East. 3, 115, 420.647 North. 6, 912, 370.900


Lat. 32° 34′ 29.10667″ N Lon. 94° 46′ 33.28607″ W

Elev. 418.67 Convergence 2° 01.866

AZIMUTH MARKER FOR CSM 1204

0.99990703

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is located on US Highway 259, north of Loop 281 and in front of Z Team Motor Sports, between the parking lot and the drainage ditch.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:


GEODETIC POSITION:

East. 3, 128, 207.082 Lat. 32° 34′ 12.55134″ N North. 6, 911, 152.806 Lon. 94° 44′ 04.45884″ W

Elev. 397.59 Convergence 2° 03.219

Scale Factor 0.99990769

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is on the east side of US 259, between Janet Kay Drive and Henderson Lane.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. *3,* 129, 183.908 6, 907, 968.344

Lat. 32° 33′ 40.71312″ N Lon. 94° 43′ 54.38532″ W

Elev.

391.28

Convergence

2°03.310'

Scale Factor

0.99990899

CSM 1305
AZIMUTH MARKER FOR CSM 1205

NTS

GENERAL LOCATION:

The marker is located on FM 2879 south of FM 449 approximately ?? miles, on the west side of the road in front of a residence, on the crest of a hill.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 142, 179.410 6, 920, 001.292

Lat. 32° 35′ 35.06971″ N Lon. 94° 41′ 17.53087″ W

Elev.

387.65

Convergence

2°04.736'

Scale Factor

0.99990444

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK POSTED SIGN CR 3633 (OLD FM 2879) CR 3633 (OLD FM 2879) POWER POLE

GENERAL LOCATION:

The marker is in the right of way of FM 2879 adjacent to the intersection with CR 3633 (Old FM 2879)

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 141, 973.539 6, 916, 603.973 Lat. 32° 35′ 01.54744″ N Lon. 94° 41′ 21.37597″ W

Elev.

387.87


Convergence

2° 04.701'

Scale Factor

0.99990574

CSM 1306
AZIMUTH MARKER FOR CSM 1206



GENERAL LOCATION:

The marker is located at the intersection of State Highway 300 and FM 1844, on the southeast side of the intersection.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 10: North. 6. 91:

3, 101, 697. 394 6, 917, 832. 555

Lat. 32° 35° 27.90371″ N Lon. 94° 49′ 11.33388″ W

Elev.

435.81

Convergence


2° 00`. 429'

Scale Factor

0.99990471

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW

2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is located north of the intersection of State Highway 300 and FM 1844, approximately 1800' on the east side of SH 300.

Marker is a 5/8" x 5 rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER -JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North.

3, 100, 125.004 6, 919, 064, 837

Lat. 32° 35′ 40.63493″ N 94° 49′ 29.19850″ W Lon.

Elev.


454.24

Convergence

2°00.267'

Scale Factor 0.99990422

AZIMUTH MARKER FOR CSM 1207



GENERAL LOCATION:

The marker is in the right of way on the south side of Loop 281, east of the Tuttle Street entrance io Longview Mall.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 123, 580.752 6, 900, 616.487

Lat. 32° 32′ 29.99250″ N Lon. 94° 45′ 02.88229″ W

Elev.

349.73

Convergence

2°02.688'

Scale Factor

0.99991196

EXPRESS LUBE LONGVIEW HIGH SCHOOL

CSM 1308

A 51'

A 751'

A

LOOP NO. 281

GENERAL LOCATION:

The marker is located on the north side of Loop 281 between the entrance for the Longview Highschool Bodyshop, and the entrance for the Texaco Xpress Lube, east of Judson Road.

Marker is a 5/8" x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 125, North. 6, 900.

3, 125, 351.301 6, 900, 968.324 Lat. 32° 32' 32.84626" N Lon. 94° 44' 42.06414" W

Elev.

384.37


Convergence

2° 02.877'

Scale Factor 0.99991184

CSM 1308
AZIMUTH MARKER FOR CSM 1208

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is north of Loop 281 on Alpine Road (FM 2208) at the intersection of Alpine and FM 2879. On the East side of Alpine.

Marker is a 5/8" x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

Scale Factor

GEODETIC POSITION:

East. 3, 139, 084.195 North. 6, 900, 276.100

Lat. 32° 32' 21.11573" N Lon. 94° 42' 02.02524" W


Elev. 411.92 Convergence 2° 04.332

CSM 1209

0.99991234

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK





GENERAL LOCATION:

The marker is located on the south side of FM 2208, .7 mile from Alpine Road.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100.000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

Convergence

GEODETIC POSITION:

East. 3, 141, 168.889 North. 6, 901, 393.294

141,168.889 Lat. 32° 32′ 31.41713″ N 901,393.294 Lon. 94° 41′ 37.21465″ W

Elev. 424.43

2°04.557'

Scale Factor 0.99991190


CSM 1309 AZIMUTH MARKER FOR CSM 1209

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK





US HIGHWAY 80 WEST BOUND



US HIGHWAY 80 EAST BOUND

TO HALLSVILLE

TRINITY INDUSTRIES

GENERAL LOCATION:

The marker is located east of Longview on US Highway 80 in the median west of the Trinity entrance between Hall and Lawrence Roads.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 155, 286. 198 6, 888, 057. 028

Lat. 32° 30′ 14.44539″ N Lon. 94° 38′ 58.10826″ W

Elev.

340.41

Convergence

2 06.003

Scale Factor

0.99991798

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK INSURANCE AUTO AUCTION 25.81 NO PARKING CSM 1310, SIGN ΕP ന US HIGHWAY 80 WEST BOUND S CROSS OVER TO LONGVIEW TO HALLSVILLE **US HIGHWAY 80 EAST BOUND**

GENERAL LOCATION:

The marker is located in the center median of US HIghway 80 east of Longview, near the cross over at the Auto Auction.

Marker is a 5/8" x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 157, 377.344 6, 888, 635.706 Lat. 32° 30′ 19.40891″ N Lon. 94° 38′ 33.45714″ W

Elev.

368.22

Convergence

2°06.227'

Scale Factor

0.99991775

CSM 1310
AZIMUTH MARKER FOR CSM 1210

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK TO LONGVIEW US HIGHWAY 80 WEST BOUND US HIGHWAY 80 EAST BOUND TO HALLSVILLE TO HALLSVILLE CITY OF LONGVIEW 12.3' CSM 1210 TO HALLSVILLE CITY OF LONGVIEW 12.3' CSM 1210 TO HALLSVILLE

GENERAL LOCATION:

The marker is located east of Longview at the intersection of US Highway 80 and Mt. Pleasant Raod.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. *3*, 167, 514.611 6, 890, 977.533

Lat. 32° 30′ 38.86848″ N Lon. 94° 36′ 34.14521″ W

Elev.

396.268

Convergence

2°07.312'

Scale Factor

0.99991687


CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK

SHIRLEY EQUIPMENT CO.



TO LONGVIEW

US HIGHWAY 80 WEST BOUND



US HIGHWAY 80 EAST BOUND

TO HALLSVILLE

GENERAL LOCATION:

The marker is located in the center median of US Highway 80 east of Longview, near the crossover at Shirely Equipment Company.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 165, 257.939 6, 890, 442.567 Lat. 32°30′34.40434″N Lon. 94°37′00.71256″W

Elev.

398.60

Convergence


2°07.070'

Scale Factor

0.99991707

CSM 1311 AZIMUTH MARKER FOR CSM 1211

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is in the median of loop 281, south of Page Road and east of ROMCO Equipment Co.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS -2002 - SURVEY MARKER -JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 144, 780.300 North.

6, 892, 384. 382

32° 31' 01.03142" N Lat. 94 ° 40 ′ 58.87510 " W Lon.

Elev.


373.19

Convergence 2° 04.906'

Scale Factor

0.99991586

M1212



GENERAL LOCATION:

The marker is in the median of LOOP 281, 383 feet northwest of Mona Drive.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

Elev.

GEODETIC POSITION:

East. 3, 146, 767.737 North. 6, 890, 086.318

323.38


Convergence 2° 05.108

Scale Factor 0.99991692

Lat. 32° 30′ 37.59089″ N Lon. 94° 40′ 36.65519″ W

CSM 1312
AZIMUTH MARKER FOR CSM 1212

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



EAST MARSHALL AVENUE

GENERAL LOCATION:

The marker is on the grounds of the Longview Wellness Center in a curbed grassy area between the building and Marshall Avenue.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW. TEXAS - 2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

North.

3, 132, 151.752 6, 887, 002.599 Lat. 32° 30′ 12.32531″ N Lon. 94° 43′ 28.53056″ W

Elev.

378.04

Convergence

2 °03.545

Scale Factor

0.99991808

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK

> .5 5


JOHNNY CACES

TO DOWNTOWN

TO US 259

I\I NTS

US HIGHWAY 80



LONGVIEW COMMONS



RAGLAND SALES

GENERAL LOCATION:

The marker is located south of US Highway 80 at the Ragland Sales and across the street from Johnny Caces.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS -2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. *3, 134, 330.567 6, 887, 259, 972*

Lat. 32° 30′ 14.09511″ N Lon. 94° 43′ 02.99575″ W

Elev.

377.36

Convergence

2°03.777'

Scale Factor

0.99991800

CSM 1313
AZIMUTH MARKER FOR CSM 1213

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK COTTON STREET FIRE HYD R CSM 1214

GENERAL LOCATION:

The marker is on the south east corner of the intersection of Cotton Street and Eastman Road (US Highway 259), across Eastman Road from the Chevron Station.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.


GRID POSITION:

GEODETIC POSITION:

East. 3, 137, 652.912 Lat. 32° 29' 30.93235" N North. 6, 883, 015.131 Lon. 94° 42' 26.01335" W

Elev. 342.41

Convergence 2°04.113° Scale Factor 0.99992000



GENERAL LOCATION:

The marker is located on US Highway 259, (Eastman Road), south of the intersection of US 259 and Cotton Street, on the west side of the road.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 137, 652.988 6, 881, 358.098 Lat. 32°29′14.54578″N Lon. 94°42′26.71078″W

Elev.

336.53

Convergence

2° 04.107'

Scale Factor

0.99992078

CSM 1314
AZIMUTH MARKER FOR CSM 1214

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK

WESTBOUND

LANES

I\I NTS

IH 20

EASTBOUND

LANES

CSM 1215

SERVICE ROAD

GENERAL LOCATION:

The marker is located east of Longview on the srevice road for I-20, east of the intersection of Lansing Switch Road and the service road. There is not an exit for Lansing Switch Road from I-20.

Marker is a 5/8 " x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 165, 470.053 6, 874, 953.365

Lat. 32°28' 01.15751" N Lon. 94°37' 04.91978" W

Elev.

340.84

Convergence

2 °07, 032 '

Scale Factor

0.99992432

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK CSM 1315 A 35' OVER 10 STORY OF LANES WESTBOUND LANES LANES LANES

GENERAL LOCATION:

The marker is located on the north side of Interstate 20 at Lansing Switch Road and on the west side of Lansing Switch. Note, there is no exit for Lansing Switch off of the Interstate.

Marker is a 5/8" x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA O7F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 164, 301.519 6, 874, 921.905 Lat. 32°28' 01.27339" N Lon. 94°37' 18.56403" W

Elev.

374.75


Convergence

2 06.908

Scale Factor

0.99992431

CSM 1315
AZIMUTH MARKER FOR CSM 1215



The marker is located on Gum Springs Road (FM 968) east of US Highway 259 (Eastman Road) at the intersection of Gum Springs Road and Robert Wilson Road, approximately .6 miles west of Loop 281.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North.

3, 143, 889.853 6, 872, 663.417 Lat. 32°27′46.33039″N Lon. 94°41′17.62337″W

Elev.

330.91

Convergence


2°04.735

Scale Factor

0.99992505

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK





GENERAL LOCATION:

The marker is located south of the intersection of Robert Wilson Road and Neiman-Marcus Drive, on the west side of the street.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 145, 377.065 6. 872, 747.287 Lat. 32°27′46.62558″N Lon. 94°41′00.24025″W

Elev.

347.63

Convergence


2° 04.893'

Scale Factor

0.99992503

CSM 1316
AZIMUTH MARKER FOR CSM 1216

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is located on Tally Road, at the intersection of Tally and Timberlake Road (CR 3322) on the north side of the pavement.

Marker is a 5/8 " \times 5' rebar placed in concrete with a 3-1/4 aluminum cap imprinted CITY OF LONGVIEW. TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE. and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 157, 422.996 North. 6, 860, 591.651 Lat. 32° 25′ 42.06838″ N Lon. 94° 38′ 44.93661″ W

Elev. 264.40 Convergence 2°06.123°

Scale Factor 0.99993136

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK FENCE CORNER X TALLEY ROAD TIMBERLAKE LANE 2180'

GENERAL LOCATION:

The marker is located on Tally Road, 2180' east of Timberlake Lane.

Marker is a $5/8\text{"} \times 5\text{'}$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 159, 548, 781 6, 860, 099, 492

Lat. 32° 25′ 36.42923″ N Lon. 94° 38′ 20.36142″ W

Elev.

257.74


Convergence

2°06.346'

Scale Factor

0.99993166

CSM 1317
AZIMUTH MARKER FOR CSM 1217



The marker is south of the Eastman Entrance behind the concrete barrier for the curve in Kodak Bulv.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS -2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:


GEODETIC POSITION:

East. 3, 139, 815.983 Lat. 32° 26′ 08.72995″ N North. 6, 862, 646.259 Lon. 94° 42′ 09.36874″ W

Elev. 288.85

Convergence 2°04.265°

Scale Factor 0.99992998



GENERAL LOCATION:

The marker is located on the north side of Kodak Bulvd. and approximately 1600' west of the curve at the Texas Eastman Entrance.

Marker is a 5/8" x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100.000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

Scale Factor

GEODETIC POSITION:

East. 3, 137, 341.084 North. 6, 862, 609, 236 Elev.


288.45

Convergence 2° 04.002'

0.99992995

32°26' 09.24797" N 94°42' 38.24422" W Lat. Lon.

AZIMUTH MARKER FOR CSM 1218



The marker is located on the south side of State Highway 149, and east of FM 322 in front of Citizens National Bank, in Lakeport.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:


GEODETIC POSITION:

East. 3, 138, 635.122 Lat. 32° 24' 53.53909" N North. 6, 855, 000.148 Lon. 94° 42' 26.35913" W

Elev. 264.16

Convergence 2°04.110°

Scale Factor 0.99993393



The marker is located on the north side of State Highway 149, and south of the intersection with Milam Road, in front of CUDD Pressure Controls, south of Longview.

Marker is an aluminum cap in concrete imprinted "STATE DEPT. OF HWYS. AND PUBLIC TRANS. — SURVEY MONUMENT" and field stamped "AZ.MK." this marker is an "azimuth marker" to a Satellite Station which is located at the intersection of SH 149 and SH 322 and is presently unsuitable for GPS observations.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 140, 694.768 Lat. 32°24' 36.20804" N North. 6, 853, 322.054 Lon. 94°42' 03.05503" W

Elev. 292.63

Convergence 2° 04.322'

Scale Factor 0.99993486


CSM 1319
AZIMUTH MARKER FOR CSM 1219

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



INTERSTATE HIGHWAY 20

(WEST BOUND LANE)



GENERAL LOCATION:

The marker is located west of the Estes Parkway overpass. and west of the Sabine River Bridge, approximately 2000 feet. in the ceter median .

Marker is a $5/8\,^\circ$ x $5\,^\circ$ rebar placed in concrete with a $3-1/4\,^\circ$ aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North.

3, 119, 417.655 6, 860, 435.120 Lat. 32° 25′ 54.09473″ N Lon. 94° 46′ 08.15537″ W

Elev.


277.60

Convergence


2°02.094'

Scale Factor

0.99993074



INTERSTATE HIGHWAY NO. 20 (WBL)



INTERSTATE HIGHWAY NO. 20 (EBL)

GENERAL LOCATION:

The marker is located in the median of Interstate Highway 20, just west of the Sabine River Bridge, approximately 200'.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North.

3, 121, 936.289 6, 860, 990.376 Lat. 32° 25° 58.69985" N Lon. 94° 45° 38.55576" W

Elev.

276.24

Convergence


2°02.363'

Scale Factor

0.99993050

CSM 1320
AZIMUTH MARKER FOR CSM 1220

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is located in the median of State Highway No. 31 north of Interstate Highway 20, at the crossover just north of Oakwood Mobilehome Sales.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 108, 590.040 North. 6, 868, 016.510 Lat. 32°27′12.85681″N Lon. 94°48′11.30255″W

Elev.

264.31

Convergence

2 °00, 975 '

Scale Factor

0.99992671

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK AND THE SELECTION OF THE SELECT

ARPHO 7 3500 CAST ORS IN CHINAY NO. 31

GENERAL LOCATION:

The marker is located in the center median of US Highway 31, south of the Sabine River Bridge, at the crossover just south of the MAC Truck Sales.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 107, 433.826 Lat. 32° 27' 02.72924" N North. 6, 866, 951.745 Lon. 94° 48' 25.22510" W

Elev. 265.33 Convergence 2°00.848'

Scale Factor 0.99992722

CSM 1321
AZIMUTH MARKER FOR CSM 1221

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK BRICK SIGN SAFETY-KLEEN SAFETY-KLEEN TO AZM 1322 FM 1845 (LOOP 281 SOUTH)

GENERAL LOCATION:

The marker is east of Michael Drive and north of FM 1845 in front of Saftey-Kleen.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 123, 223.824 6, 872, 655.723 Lat. 32°27′53.60766″N Lon. 94°45′18.69102″W

Elev.


266.39

Convergence

2 02.544

Scale Factor

0.99992469



The marker is located on the north side of FM 1845 in front of DARR Equipment Company.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 121, 632.209 6, 873, 482.639 Lat. 32° 28' 02.34618" N Lon. 94° 45' 36.91377" W

Elev.

283.08

Convergence

2°02.378'


Scale Factor

0.99992426

CSM 1322 AZIMUTH MARKER FOR CSM 1222

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW

2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is located in the median of State Highway 31, just north of the FM 1845 overpass, close to the gard rail.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of \pm 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 119, 128.298 6, 877, 655.867 Lat. 32°28′44.49735″N Lon. 94°46′04.39269″W

Elev.

328.08

Convergence


2 °02. 128 '

Scale Factor

0.99992221

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW

2002 HORIZONTAL & VERTICAL CONTROL NETWORK



GENERAL LOCATION:

The marker is located in the center median of US Highway 31, south of the intersection of US 31 and FM 1845, at the crossover south of the convience store.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

Scale Factor

GEODETIC POSITION:

East. 3, 117, 793.868 Lat. 32° 28' 25.59283" N North. 6, 875, 696.856 Lon. 94° 46' 20.77273" W

Elev. 291.56


Convergence 2° 01.980'

0.99992312

CSM 1323
AZIMUTH MARKER FOR CSM 1223



U.S.HIGHWAY NO. 80 (WEST MARSHALL)



GENERAL LOCATION:

The marker is located at the intersection of US Highway 80 and H.G. Mosley, on the south east corner of the intersection.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 116, 521.754 6, 886, 984.087 Lat. 32° 30′ 17.66218″ N Lon. 94° 46′ 30.94283″ W

Elev.

324.06

Convergence

2 "01.887"


Scale Factor

0.99991783

VOYLES AUTO SALES



U. S. HIGHWAY NO. 80 (WEST MARSHALL)



LONGVIEW AUTO PARTS

GENERAL LOCATION:

The marker is located on the south side of US Highway 80, just west of the intersection of SH 300, (Gilmer Road), in front of Longview Automotive.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 118, 164.086 6, 886, 733.659

Lat. 32° 30′ 14.60912″ N Lon. 94° 46′ 11.88008″ W

Elev.

316.11


Convergence

2°02.060'

Scale Factor

0.99991797

CSM 1324
AZIMUTH MARKER FOR CSM 1224



The marker is located east of intersection of H.G. Mosley and Bill Owens Parkway, aproximately 100', and on the north side of the pavement.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 119, 920.270 6, 894, 097.508 Lat. 32° 31′ 26.81491″ N Lon. 94° 45′ 48.32713″ W

Elev.

326.05

Convergence


2°02.274'

Scale Factor

0.99991472

CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK





H. G. MOSLEY PARKWAY

GENERAL LOCATION:

The marker is located near the intrance of Wild Wood Addition, at the intersection of H.G. Mosley and Enchanted Drive, near the angle point of a wood privacy fence.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3. North. 6.

3, 118, 758.973 6, 893, 356.038 Lat. 32° 31′ 19.89074″ N Lon. 94° 46′ 02.19043″ W

Elev.

341.46

Convergence

2°02.148

Scale Factor


0.99991502

CSM 1325 AZIMUTH MARKER FOR CSM 1225

2002 HORIZONTAL & VERTICAL CONTROL NETWORK



BLUERIDGE PARKWAY



GENERAL LOCATION:

The marker is located on the east side of State Highway 300, (Gilmer Rd.) at the intersection of SH 300, and Blueridge Parkway.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 111, 125.660 6, 899, 256.725 Lat. 32° 32′ 20.91928″ N Lon. 94° 47′ 28.85916″ W

Elev.


412.82

Convergence

2°01.361


Scale Factor

0.99991235



EVERGREEN STREET

DOLLAR GENERAL



GENERAL LOCATION:

The marker is located at the intersection of State Highway 300 and Evergreen Street, north of Loop 281. on the south west corner of the intersection.

Marker is a 5/8" x 5' rebar placed in concrete with a 3–1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS – 2002 – SURVEY MARKER – JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 111, 861.355 6, 897, 108, 347 Lat. 32° 31′ 59.41615″ N Lon. 94° 47′ 21.15633″ W

Elev.

405.60


Convergence

2°01.431'

Scale Factor

0.99991328

CSM 1326
AZIMUTH MARKER FOR CSM 1226



NTS

GENERAL LOCATION:

The marker is located north of FM 2275, George Richie Road, on White Oak Road, across from Morgan Road, in front of a residence.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.


GRID POSITION:

GEODETIC POSITION:

East. 3, 085, 147.076 Lat. 32° 34' 12.46089" N North. 6, 909, 628.306 Lon. 94° 52' 27.98452" W

Elev. 446.42

Convergence 1° 58.642 Scale Factor 0.99990770



The marker is located north of George Richie Road on White Oak Road and north of East mountain Road, in front of native stone fence.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. *3, 087, 230.370 6, 908, 851.436*

Lat. 32°34′04.06595″N Lon. 94°52′03.96699″W

Elev.

418.07


Convergence

1°58.860'

Scale Factor

0.99990804

CSM 1327
AZIMUTH MARKER FOR CSM 1227



The marker is on the east side of State Highway 42 south of US 80 and south of the railroad, near the golf course.

Marker is a $5/8" \times 5"$ rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER - JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet, Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. *3,* 093, 493, 608 6, 880, 705, 769

Lat. 32° 29° 23.56919″ N Lon. 94° 51° 02.24264″ W

Elev.


319.36

Convergence

1° 59.421

Scale Factor

0.99992035



The marker is south of Harrison Road north of the Amoco Pipeline Co. driveway. For reference .5 mile north of Sabine River bridge on State Highway No. 42.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 093, 588.396 6, 877, 430.762 Lat. 32°28′51.14821″N Lon. 94°51′02.46463″W

Elev.

303.48


Convergence

1° 59.419'

Scale Factor

0.99992189

CSIM 1328 AZIMUTH MARKER FOR CSM 1228



The marker is located on the south east corner of the intersection of FM 2275 (George Richie Road) and FM 1845 (Pine Tree Road)

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW. TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100.000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North 3, 098, 555.396 6, 905, 169.266 Lat. 32° 33′ 23.75759″ N Lon. 94° 49′ 53.20630″ W

Elev.


400.17

Convergence

2°00.049

Scale Factor

0.99990970



The marker is located north of the intersection of FM 1845 and George Richie Road, past the bridge and in front of a brick house.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet. Vertical Datum is NAVD 88 and referenced to NGS Station: E-160. Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North. 3, 095, 668.224 6, 908, 799.119

Lat. 32° 34′ 00.65135″ N Lon. 94° 50′ 25.44375″ W

Elev.

388.56


Convergence

1°59.755'

Scale Factor

0.99990818

CSM 1329
AZIMUTH MARKER FOR CSM 1229



The marker is located north of US Highway 80 in White Oak, on Whatley Road north of Rocking B Ranch Road, in front of a brick residence, house No. 341.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4" aluminum cap imprinted CITY OF LONGVIEW, TEXAS - 2002 - SURVEY MARKER -JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet,

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. North.

3, 097, 656.863 6, 893, 600.480

32° 31′ 29.65821″ N 94° 50′ 08.41282″ W Lat. Lon.

Elev.

351.90

Convergence

1° 59.910

Scale Factor

0.99991459

CITY SURVEY MARKER - SITE SKETCH CITY OF LONGVIEW 2002 HORIZONTAL & VERTICAL CONTROL NETWORK CSM 1330 CSM 1330 WHATLEY ROAD WHATLEY ROAD WHATLEY ROAD

GENERAL LOCATION:

The marker is located north of US Highway 80 in White Oak on Whatley Road south of Rocking B Ranch Road, on the east side of the pavement.

Marker is a 5/8" x 5' rebar placed in concrete with a 3-1/4"aluminum cap imprinted CITY OF LONGVIEW, TEXAS — 2002 — SURVEY MARKER — JOHNSON & PACE, and field stamped with the marker number.

Horizontal Datum is the Texas Coordinate System of 1983, North Central Zone, (which is based upon NAD 83), and referenced to NGS Stations: "FAA 07F A 1994", "FAA GGG A", 4F4 A 1994', 'FAA ASL A 1994" and "FAA F12 A 1994".

Horizontal Accuracy is within a tolerance of 1 foot in 100,000 feet.

Vertical Datum is NAVD 88 and referenced to NGS Station: E-160.

Vertical Accuracy is within a tolerance of +/- 0.10 foot.

GRID POSITION:

GEODETIC POSITION:

East. 3, 098, 6 North. 6, 893, 2

3, 098, 601.786 6, 893, 217.064 Lat. 32°31′25.54020″N Lon. 94°49′57.53885″W

Elev.

355.93

Convergence

2°00.009

Scale Factor

0.99991477

CSM 1330
AZIMUTH MARKER FOR CSM 1230